

# B4 FOURline

Rigid profile / LED tape



## B4 FOURline - Rigid LED profile range

- High CRI90+ available in 2700k, 3000k & 4000k
- 7.2w up to 19.2w 2520lm per meter 24V input voltage
- 3-Step MacAdam binning,
- surface mounted, recessed or corner mount profiles
- opal or clear polycarbonate diffuser options

B4-S8 - slim surface mount	B4-S15 - surface mount	B4-S35 - surface mount large	B4-C18 - corner profile
B4-R8 - slim recessed mount	B4-R15 - recessed mount	B4-R35 - recessed mount large	B4-S7 - surface micro profile

## OPTIONS & TECHNICAL PARAMETERS

	SO	HO	HO+	UO	RGBW	EQ6W	EQ12W
Wattage (p/m)	7.2w	9.6w	14.4w	19.2w	26.9w	6w	12w
Voltage	24vDC	24vDC	24vDC	24vDC	24vDC	24vDC	24vDC
CRI	CRI90	CRI90	CRI90	CRI90	CRI90	CRI90	CRI90
Cutting Interval	100mm	50mm	50mm	33.3mm	72mm	50mm	50mm
Colour temp options	27 / 30 / 4000K	27 / 30 / 4000K	27 / 30 / 4000K	27 / 30 / 4000K	RGB + 3000K	27 / 30 / 4000K	27 / 30 / 4000K
Lumen output (p/m)	up to 980lm @ (4000K)	up to 1100lm @ (4000K)	up to 1960lm @ (4000K)	up to 2520lm @ (4000K)	up to 1300lm	up to 550lm @ (4000K)	up to 1050lm @ (4000K)

# Technical Data Sheet - Rigid LED profile

## SPECIFICATION CONFIGURATOR

PRODUCT CODE	B4-S15	OP	HO	927	S	ND	5000MM
B4-S8 - slim surface mount profile							
B4-S15 - surface mount profile							
B4-S35 - surface mount large							
B4-R8 - slim recessed profile							
B4-R15 - recessed profile							
B4-R35 - recessed large profile							
B4-C18 - corner mounted profile							
B4-S7 - surface mounted micro profile							
<b>DIFFUSER</b>							
OP - opal polycarbonate diffuser							
CLR - clear polycarbonate diffuser							
<b>LED STRIP</b>							
LO - low output B4 4.8w tape							
SO - standard output B4 7.2w tape							
HO - high output B4 9.6w tape							
HO+ - high output plus B4 14.4w tape							
UO - ultra output B4 19.2w tape							
RGBW - RGB+ warm white B4 26.9w tape							
EQ6W - lumino EQ 6w tape							
EQ12W - lumino EQ 12w tape							
<b>COLOUR TEMP</b>							
27K - extra warm white 2700k							
3K - warm white 3000k							
4K - cool white 4000k							
<b>FINISH</b>							
ALUMINIUM							
BLACK							
WHITE							

ND - Remote Non Dim Driver  
1-10V - Remote 1-10V Dim Driver  
Dali - Remote Dali Driver

length based on cutting increments of led tape selected as per led strip data

**B4-S15-OP-HO-927-S-ND-5000MM**  
B4 FOURline surface mounted Aluminium profile, opal polycarbonate diffuser, high output 9.6w tape, 2700k c/w remote 24v non dim power supply.