






Arclux

With 2 x 6.5 W high performance LEDs,
CRI: > 80, Colour tolerance: max. 2 SDCM
Service life: L90/B10 > 50 000 h
protection class I, IP67  , IK08
light directed by a high-end optical system,
corrosion-resistant die cast aluminium housing AlSi12,
polyester powder coated,
all exterior steel parts are stainless steel,
tempered high transmission safety glass,
silicon gasket, 2 drilled holes Ø 6 mm,
spacing 259 mm, 2 x M20 cable glands,
4 x M6 grub screws to offset inclined surfaces,
integral driver (AC)



Arclux

Part number	Colour	Light source*	Luminous flux	Main beam angle γ	
8 375 046 009	black	2 x LED 6.5 W warm white (3000 K)	930 lm	C 0 – 180	C 90 – 270
8 375 066 009	white			10°	180°
8 375 056 009	silver grey				




Part number	Colour	Light source*	Luminous flux	Main beam angle γ	
8 375 045 009	black	2 x LED 6.5 W neutral white (4000 K)	977 lm	C 0 – 180	C 90 – 270
8 375 065 009	white			10°	180°
8 375 055 009	silver grey				

* Luminaires available in 2700 K or other colour temperatures on request

Part number	Description
... 1 ...	Dimmable luminaire (DALI)

Arclux RGBW

With 2 x 4 x 1.5 W RGBW high performance LEDs
for external DMX signal
protection class I, IP67  , IK08
homogeneous colour mixing achieved using light
conductor technology, light directed by a high-end
optical system, 3 preset colour changing sequences
and the individual colours available without the
use of an external DMX signal, corrosion-resistant
die cast aluminium housing AlSi12,
polyester powder coated, all exterior steel parts are
stainless steel, high efficiency safety glass,
silicone gasket, 2 fixing holes Ø 6 mm,
spacing 259 mm, cable entries: 2 x M20,
4 x M6 grub screws to offset inclined surfaces,
integral DMX 512 addressable driver



Arclux RGBW

Part number	Colour	Light source*	Luminous flux	Main beam angle γ	
8 374 049 009	black	2 x LED RGBW max. 12 W	max. 106 lm	C 0 – 180	C 90 – 270
8 374 069 009	white			12°	180°
8 374 059 009	silver grey				

*The luminaires are available with LEDs in different colour combinations upon request.

LED (see page 185)

