



SMART CAKE/KUP/LOTIS

more info? supermodular.com/en/smart-cake
supermodular.com/en/smart-kup
supermodular.com/en/smart-lotis

Designers can stay up all night trying all sorts of things with Smart, our most versatile range of architectural lighting. Mix and match, from a mosaic of shapes, sizes, colours and mounting options, and create a playful installation while maintaining a consistent look and feel. The Smart choice for any application.

3 designs that multiply

Smart's 3 designs are a party for designers. Double the fun, Lotis, Cake and Kup come in fixed and adjustable versions. Adding colour to fun, all variations come in black structure, white structure and a warm, golden finish, and can further be combined with all Smart accessories.


Limitless combinations

Play with shapes and depth. Smart mask is the opportunity to play with round lights in a square or rectangular shape. Smart box adds dimension by protruding from the ceiling, hugging any of the 3 designs. Smart tubed, suspended, surface-mounted on wall or ceiling, gives depths to the circular design, emitting down/up light. Smart tubed 82 easily slides in our 230V track rail.

Join the ball


Smart ball flaunts a bubbly, spherical shape, in two sizes: Smart ball 82 and Smart ball 115. In white or black structure, it hangs gracefully from a thin matte black suspension cable. As with the other accessories, combine Smart ball with a differently coloured light in any of the 3 designs, for a little contrast and fun. Smart is also warm-dim compatible.

Smart kup 115 LED GE



1X LED ARRAY INCL. 16.25W


! 3500K ON REQUEST



CONNECTED > SEE GOODIES
INSTALLATION ACCESSORIES


10889830	CONBOX 190X192X130X256
12290530	GYPKIT 190X190 - Ø108
12810230	RECESSED RING Ø127 H100

Smart kup 115 IP54 LED GE



1X LED ARRAY INCL. 16.25W

! 3500K ON REQUEST



CONNECTED > SEE GOODIES
INSTALLATION ACCESSORIES

10889830	CONBOX 190X192X130X256
12290530	GYPKIT 190X190 - Ø108
12810230	RECESSED RING Ø127 H100



	2700K / CRI90+			
	15°	25°	40°	65°
black struc	12761232	12761032	12761332	12760032
gold	12761246	12761046	12761346	12760046
white struc	12761209	12761009	12761309	12760009
	3000K / CRI90+			
	15°	25°	40°	65°
black struc	12761432	12761532	12761632	12760132
gold	12761446	12761546	12761646	12760146
white struc	12761409	12761509	12761609	12760109
	4000K / CRI90+			
	15°	25°	40°	65°
black struc	12761732	12761132	12761832	12760232
gold	12761746	12761146	12761846	12760246
white struc	12761709	12761109	12761809	12760209

LUMINAIRE OUTPUT & POWER CONSUMPTION
(white struc)

	350mA	500mA	700mA
2700K / 25°	1065lm / 11W	1461lm / 16.25W	1943lm / 23.6W
3000K / 25°	1046lm / 11W	1434lm / 16.25W	1908lm / 23.6W
4000K / 25°	1219lm / 11W	1672lm / 16.25W	2224lm / 23.6W




	2700K / CRI90+			
	15°	25°	40°	65°
black struc	12762232	12762032	12762332	12760332
gold	12762246	12762046	12762346	12760346
white struc	12762209	12762009	12762309	12760309
	3000K / CRI90+			
	15°	25°	40°	65°
black struc	12762432	12762532	12762632	12760432
gold	12762446	12762546	12762646	12760446
white struc	12762409	12762509	12762609	12760409
	4000K / CRI90+			
	15°	25°	40°	65°
black struc	12762732	12762132	12762832	12760532
gold	12762746	12762146	12762846	12760546
white struc	12762709	12762109	12762809	12760509

LUMINAIRE OUTPUT & POWER CONSUMPTION
(white struc)

	350mA	500mA	700mA
2700K / 25°	1029lm / 11W	1412lm / 16.25W	1878lm / 23.6W
3000K / 25°	1011lm / 11W	1386lm / 16.25W	1844lm / 23.6W
4000K / 25°	1178lm / 11W	1616lm / 16.25W	2150lm / 23.6W

Smart kup 115 diffuse IP54 LED GE



1X LED ARRAY INCL. 16.25W

! 3500K ON REQUEST


DRIVER > SEE PRODUCT PAGE ON WEBSITE

SMART COMBINATIONS > SEE PAGES 320-329

CONNECTED > SEE GOODIES

INSTALLATION ACCESSORIES

10889830	CONBOX 190X192X130X256
12290530	GYPKIT 190X190 - Ø108
12810230	RECESSED RING Ø127 H100



500mA IP54 GWT 960° 0.48KG			
	2700K / CRI90+	3000K / CRI90+	4000K / CRI90+
	85°	85°	85°
black struc	12763032	12763532	12763132
gold	12763046	12763546	12763146
white struc	12763009	12763509	12763109

LUMINAIRE OUTPUT & POWER CONSUMPTION (white struc)			
	350mA	500mA	700mA
2700K / 85°	811lm / 11W	1113lm / 16.25W	1480lm / 23.6W
3000K / 85°	797lm / 11W	1092lm / 16.25W	1453lm / 23.6W
4000K / 85°	928lm / 11W	1273lm / 16.25W	1694lm / 23.6W