



SMART CAKE/KUP/LOTIS

more info? supermodular.com/en/smart-cake
supermodular.com/en/smart-kup
supermodular.com/en/smart-lotis

Designers can stay up all night trying all sorts of things with Smart, our most versatile range of architectural lighting. Mix and match, from a mosaic of shapes, sizes, colours and mounting options, and create a playful installation while maintaining a consistent look and feel. The Smart choice for any application.

3 designs that multiply

Smart's 3 designs are a party for designers. Double the fun, Lotis, Cake and Kup come in fixed and adjustable versions. Adding colour to fun, all variations come in black structure, white structure and a warm, golden finish, and can further be combined with all Smart accessories.

Limitless combinations

Play with shapes and depth. Smart mask is the opportunity to play with round lights in a square or rectangular shape. Smart box adds dimension by protruding from the ceiling, hugging any of the 3 designs. Smart tubed, suspended, surface-mounted on wall or ceiling, gives depths to the circular design, emitting down/up light. Smart tubed 82 easily slides in our 230V track rail.

Join the ball


Smart ball flaunts a bubbly, spherical shape, in two sizes: Smart ball 82 and Smart ball 115. In white or black structure, it hangs gracefully from a thin matte black suspension cable. As with the other accessories, combine Smart ball with a differently coloured light in any of the 3 designs, for a little contrast and fun. Smart is also warm-dim compatible.

Smart cake 82 LED GE



1X LED ARRAY INCL. 9.2W

! 3500K ON REQUEST



DRIVER > SEE PRODUCT PAGE ON WEBSITE

SMART COMBINATIONS > SEE PAGES 320-329

CONNECTED > SEE GOODIES

INSTALLATION ACCESSORIES

10889830	CONBOX 190X192X130X256
12290130	GYPKIT 190X190 - Ø70
12291030	GYPKIT 210X190-2XØ70 R35-88
12500230	SMART RECESSED RING 82



	2700K / CRI90+		
	15°	25°	40°
black struc	12411632	12411032	12411232
gold	12411646	12411046	12411246
white struc	12411609	12411009	12411209
	3000K / CRI90+		
	15°	25°	40°
black struc	12411732	12411432	12411532
gold	12411746	12411446	12411546
white struc	12411709	12411409	12411509
	4000K / CRI90+		
	15°	25°	40°
black struc	12411832	12411132	12411332
gold	12411846	12411146	12411346
white struc	12411809	12411109	12411309

LUMINAIRE OUTPUT & POWER CONSUMPTION
(white struc)


	350mA	500mA	700mA
2700K / 25°	513lm / 6.2W	689lm / 9.2W	885lm / 13.4W
3000K / 25°	533lm / 6.2W	716lm / 9.2W	920lm / 13.4W
4000K / 25°	583lm / 6.2W	733lm / 9.2W	943lm / 13.4W

WARM DIM

Smart cake 82 LED warm dim GE



1X LED ARRAY INCL. 6W



CONNECTED > SEE GOODIES

INSTALLATION ACCESSORIES

10889830	CONBOX 190X192X130X256
12290130	GYPKIT 190X190 - Ø70
12291030	GYPKIT 210X190-2XØ70 R35-88
12500230	SMART RECESSED RING 82




	1800K - 3000K / CRI90+	
	25°	40°
black struc	12413132	12413232
gold	12413146	12413246
white struc	12413109	12413209

LUMINAIRE OUTPUT & POWER CONSUMPTION
(white struc)


@3000K / 25°	452lm / 6W
--------------	------------

Smart cake 82 IP55 LED GE



1X LED ARRAY INCL. 9.2W

! 3500K ON REQUEST



CONNECTED > SEE GOODIES

INSTALLATION ACCESSORIES

10889830 CONBOX 190X192X130X256


12290130 GYPKIT 190X190 - Ø70

12291030 GYPKIT 210X190-2XØ70 R35-88

12500230 SMART RECESSED RING 82

WARM DIM

Smart cake 82 IP55 LED warm dim GE



1X LED ARRAY INCL. 6W

CONNECTED > SEE GOODIES

INSTALLATION ACCESSORIES

10889830 CONBOX 190X192X130X256

12290130 GYPKIT 190X190 - Ø70

12291030 GYPKIT 210X190-2XØ70 R35-88

12500230 SMART RECESSED RING 82



	2700K / CRI90+		
	15°	25°	40°
black struc	12412632	12412032	12412132
gold	12412646	12412046	12412146
white struc	12412609	12412009	12412109
	3000K / CRI90+		
	15°	25°	40°
black struc	12412732	12412332	12412432
gold	12412746	12412346	12412446
white struc	12412709	12412309	12412409
	4000K / CRI90+		
	15°	25°	40°
black struc	12412832	12412532	12412232
gold	12412846	12412546	12412246
white struc	12412809	12412509	12412209

/LUMINAIRE OUTPUT & POWER CONSUMPTION
(white struc)

	350mA	500mA	700mA
2700K / 25°	444lm / 6.2W	596lm / 9.2W	766lm / 13.4W
3000K / 25°	462lm / 6.2W	619lm 9.2W	797lm / 13.4W
4000K / 25°	505lm / 6.2W	635lm / 9.2W	816lm / 13.4W



	1800K - 3000K / CRI90+	
	25°	40°
black struc	12414132	12414232
gold	12414146	12414246
white struc	12414109	12414209

LUMINAIRE OUTPUT & POWER CONSUMPTION
(white struc)

@3000K / 25°	400lm / 6W
--------------	------------