














Gemini 2

With high performance LEDs,
thermal monitoring device,
CRI: > 80, Colour tolerance: max. 2 SDCM
Service life: L90/B10 > 50 000 h
protection class I, IP65 , IK08
windage area AW 0.017 m²
corrosion-resistant die cast aluminium housing AlSi12,
polyester powder coated,
all exterior steel parts are stainless steel,
tempered, high transmission safety glass,
silicon gasket, wall box: 2 drilled holes Ø 6 mm,
spacing 75 mm, two cable entries for recessed or
surface mounted cable Ø 7-10 mm,
integral driver (AC/DC)



Gemini 2, narrow beam

Part number*	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)	
8 338 141 009	black	1.2 kg	8 x LED 2.5 W (20 W) warm white (3000 K)	1440 lm	up	down
8 338 161 009	white				7°	7°
8 338 151 009	silver grey					

Part number*	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)	
8 338 444 009	black	1.2 kg	8 x LED 2.5 W (20 W) neutral white (4000 K)	1554 lm	up	down
8 338 464 009	white				7°	7°
8 338 454 009	silver grey					

Gemini 2, narrow/wide beam

Part number*	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)	
8 338 142 009	black	1.2 kg	8 x LED 2.5 W (20 W) warm white (3000 K)	1400 lm	up	down
8 338 162 009	white				7°	45°
8 338 152 009	silver grey					

Part number*	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)	
8 338 445 009	black	1.2 kg	8 x LED 2.5 W (20 W) neutral white (4000 K)	1511 lm	up	down
8 338 465 009	white				7°	45°
8 338 455 009	silver grey					

Gemini 2, wide beam

Part number*	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)	
8 338 242 009	black	1.2 kg	8 x LED 2.5 W (20 W) warm white (3000 K)	1400 lm	up	down
8 338 262 009	white				45°	45°
8 338 252 009	silver grey					

Part number*	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)	
8 338 545 009	black	1.2 kg	8 x LED 2.5 W (20 W) neutral white (4000 K)	1511 lm	up	down
8 338 565 009	white				45°	45°
8 338 555 009	silver grey					

Part number*	Description
8	Luminaire with asymmetrical light distribution downwards
2	Dimmable version (1-10 V)

*On request the luminaires are available as up or downlight only and with additional light distributions.

LED (see page 247)

Luminaires available in 2700 K and other colour temperatures upon request

