




Highline
with wall bracket

With high performance LEDs,
integral temperature monitoring device,
CRI: > 80, Colour tolerance: max. 2 SDCM
Service life: L90/B10 > 50 000 h
protection class I, IP67 , IK08
windage area AW 0.029 m²
corrosion-resistant die cast aluminium housing AlSi12,
polyester powder coated,
all exterior steel parts are stainless steel,
tempered safety glass,
silicon gasket, closure with 2 stainless steel screws,
wall bracket: 2 elongated holes Ø 6.5 mm,
spacing 40 mm, tilt range 180°,
M20 cable gland,
integral driver (AC/DC)

Highline, narrow beam



Part number	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)
8 730 146 019	black	1.7 kg	9 x LED 2.5 W	1508 lm	6°
8 730 166 019	white		(23 W)		
8 730 156 019	silver grey		warm white (3000 K)		

Part number	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)
8 730 145 019	black	1.7 kg	9 x LED 2.5 W	1583 lm	6°
8 730 165 019	white		(23 W)		
8 730 155 019	silver grey		neutral white (4000 K)		





Highline, wall washer

Part number	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)
8 730 146 009	black	1.7 kg	9 x LED 2.5 W	1281 lm	C 0 – 180
8 730 166 009	white		(23 W)		C 90 – 270
8 730 156 009	silver grey		warm white (3000 K)		14°





Part number	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)
8 730 145 009	black	1.7 kg	9 x LED 2.5 W	1345 lm	C 0 – 180
8 730 165 009	white		(23 W)		C 90 – 270
8 730 155 009	silver grey		neutral white (4000 K)		14°




Highline, asymmetrical beam


Part number	Colour	Weight	Light source	Luminous flux	Main beam angle γ
8 730 146 089	black	1.7 kg	9 x LED 2.5 W	1121 lm	35°
8 730 166 089	white		(23 W)		
8 730 156 089	silver grey		warm white (3000 K)		



Part number	Colour	Weight	Light source	Luminous flux	Main beam angle γ
8 730 145 089	black	1.7 kg	9 x LED 2.5 W	1177 lm	35°
8 730 165 089	white		(23 W)		
8 730 155 089	silver grey		neutral white (4000 K)		



Part number	Description
... 0 ...	Luminaire with mounting flange (for horizontal surfaces)
... 1 ...	Dimmable luminaire (DALI)
... 2 ...	Dimmable luminaire (1-10 V)



LED (see page 247)

luminaires available in 2700 K and other colour temperatures upon request