






Highline with wall arm

With high performance LEDs,
integral temperature monitoring device,
CRI: > 80, Colour tolerance: max. 2 SDCM
Service life:: L90/B10 > 50 000 h
protection class I, IP67 , IK08
windage area AW 0.035 m²
corrosion-resistant die cast aluminium housing AlSi12,
polyester powder coated,
all exterior steel parts are stainless steel,
tempered safety glass,
silicon gasket, closure with 2 stainless steel screws,
mounting plate: 4 drilled holes Ø 7 mm,
spacing 47 mm, joint with tilt range 180°,
M20 cable gland,
integral driver (AC/DC)



Highline with wall arm, wall washer

Part number	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)	
8 730 746 009	black	2.0 kg	9 x LED 2.5 W (23 W) warm white (3000 K)	1281 lm	C 0 – 180	C 90 – 270
8 730 766 009	white				14°	93°
8 730 756 009	silver grey					

Part number	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)	
8 730 745 009	black	2.0 kg	9 x LED 2.5 W (23 W) neutral white (4000 K)	1345 lm	C 0 – 180	C 90 – 270
8 730 765 009	white				14°	93°
8 730 755 009	silver grey					

Part number	Description
1 1 . .	Dimmable luminaire (DALI)
1 2 . .	Dimmable luminaire (1-10 V)

LED (see page 247)

Luminaires available in 2700 K and other colour temperatures upon request

• • • • •