



Norms: EN 60598-1, EN 60598-2-1



IP 40

960°C

230V/50Hz

PRODUCT DESCRIPTION

Areas of Application: Commercial, Business areas, Private Houses, Art and Culture spaces. Offices, Public buildings, Hotel and Restaurant services.

Mounting: Surface/Suspended.

Light Distribution: Direct.

Light Source: LED 4000K, RG1, CRI>80, MacAdam Step <3, 70.000h lifetime (@L90, B10, Ta25 °C).

Optical System: Diffuser: Opal Silicon.

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Extruded aluminium.

Surface Finish: Powder coated.

bFlex - Opal diffuser



LED	W	Lm Output	D(mm)	kg	HF	DALI
	33	2761	Ø455	3,4	90539.L012.E	90539.L012.H
	64	5796	Ø777	5,8	90539.L016.E	90539.L016.H
	94	8280	Ø1136	8,5	90539.L024.E	90539.L024.H
	128	11592	Ø1494	11,5	90539.L032.E	90539.L032.H
	158	14950	Ø1853	14,6	90539.L040.E	90539.L040.H
	224	20930	Ø2569	20,6	90539.L056.E	90539.L056.H
	256	23920	Ø2926	23,3	90539.L064.E	90539.L064.H
	344	32890	Ø4000	31,6	90539.L088.E	90539.L088.H
	512	47840	Ø5789	45,1	90539.L128.E	90539.L128.H
	736	65780	Ø7936	63,0	90539.L176.E	90539.L176.H

- For suspended application, add suspension, current supply cable and ceiling rose. Please order separately.
- For diameters above 1494mm the product is composed by more than one part.
- For help in simulating the product's implantation in its space, please check (CONFIGURATOR.INDELAGUEGROUP.COM).


Example code for order: 90539.L032.H (DALI) + W + (COLOUR/FINISH) + 3000

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

COLOUR / FINISH

Code	Description
W	White
G	Grey
B	Black
U	Blue
V	Green
T	Yellow
K	Red
N	Jungle
D	Golden eye
O	Sahara
L	Autumn
R	Rusty chain
C	Pure chocolate
1	Mist
9	Dark rock
I	Carbon

DIMENSIONS



Recessed ceiling rose T5 D90



Surface mounted ceiling rose T24 D95




Central ceiling rose T20 D95



OPTIONS

Colour temperature



3000K

Order Code
3000

Ceiling rose



Ceiling rose
Surface T24 D95
Recessed T5 D90

• To order this option indicate the required colour for the ceiling rose.

Order Code

978600
9713

Central Ceiling Rose




Central Ceiling Rose T20
For versions Ø455 and Ø777 (3I)
For versions Ø1136 (4I)
For versions Ø1494 (6I)

• To order this option indicate the required colour for the ceiling rose.

Order Code

977201
977202
977204

Current supply cable



Transparent current cable 0,75 mm2
3 x 0,75 mm2
L1500
L3000
L6000
5 x 0,75 mm2
L1500
L3000
L6000

Order Code

940400
940401
940402
940500
940501
940502

Suspension



Suspension S11 1500mm
(x3) Ø455, Ø777
(x4) Ø1136
(x6) Ø1494, Ø1853
(x8) Ø2569
(x12) Ø2926, Ø4000
(x24) Ø5789
(x32) Ø7936

• Suspension 3000mm and 6000mm under request

Order Code

9129031
9129041
9129061
9129081
9129121
9129241
9129321

SwitchDIM



• For flux control through SwitchDIM.

Order Code

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.

Acoustic moss




• Sound absorption and humidity control.

Ø455
Ø777
Ø1136

Order Code

926800
926801
926802

Acoustic panel




• Sound absorption.

Ø455
Ø777
Ø1136


Order Code

926900
926901
926902

DETAILS




Acoustic Foam



Acoustic Moss

PHOTOMETRY



TO SPECIFY:
Modular suspended or surface LED luminaire. Powder coated extruded aluminium body, off 35mm width. With bFLEX diffuser, uniform, supple and adjustable to the profile. Available in 10 different sizes (from Ø455 to Ø7935mm). Standard version with 4000K LED, RG1 (Photobiological Risk Group 1, according to IEC 62471), CRI>80, MacAdam Step<3 and 70.000 lifetime (@L90, B10, Ta 25 C). Optional 3000K, dimmable Dali driver, S11 suspension and transparent current supply cable. Possible to choose recessed ceiling rose T5 D90 or surface mounted ceiling rose T24 D95 and central surface mounted ceiling rose T20. Available in 16 colours. – as Roxo Lighting CONCEPT O 35.