






Uplight 250 with Tight Lock, externally adjustable optics

With high performance LED module (Zhaga),
integral temperature monitoring device,
CRI: > 80, Colour tolerance: 3 SDCM
Service life: L80/B10 > 50 000 h
Protection class I, IP67 , IK10
corrosion-resistant cast aluminium housing AlSi12,
double powder coated,
with polypropylene installation sleeve,
highly efficient aluminium reflector,
externally adjustable reflector system,
tilt range 0-20°,
with Heatslide mechanism for optimal heat dissipation,
all exterior steel parts are stainless steel,
tempered safety glass, for loads up to max. 4500 kg
(according to DIN EN 60598-2-13),
silicon gasket,
V4A stainless steel trim ring closure with 2 screws,
M20 cable gland, with 0.8 m cable H07RN-F3G1,
integral driver (AC)





Uplight 250, narrow beam, with Tight Lock, externally adjustable optics

Part number	Weight	Light source	Luminous flux	Tilt range	Beam angle γ (FWHM)
8 667 016 019	5.4 kg	1 x LED module 18 W warm white (3000 K)	1841 lm	0 – 20°	9°





Uplight 250, medium wide beam, with Tight Lock, externally adjustable optics

Part number	Weight	Light source	Luminous flux	Tilt range	Beam angle γ (FWHM)
8 667 016 049	5.4 kg	1 x LED module 18 W warm white (3000 K)	1790 lm	0 – 20°	28°



Uplight 250, wide beam, with Tight Lock, externally adjustable optics

Part number	Weight	Light source	Luminous flux	Tilt range	Beam angle γ (FWHM)
8 667 016 059	5.4 kg	1 x LED module 18 W warm white (3000 K)	1774 lm	0 – 20°	55°





Uplight 250, wall washer, with Tight Lock, externally adjustable optics

Part number	Weight	Light source	Luminous flux	Tilt range	Beam angle γ (FWHM)
8 667 016 009	5.4 kg	1 x LED module 18 W warm white (3000 K)	759 lm	0 – 20°	C 0 – 180 25° C 90 – 270 75°



overlapping
trim ring

trim ring for
flush mounting



Part number	Description
... 1 ...	Luminaire with slip resistant glass (R13 according to DIN EN 51130) The light distribution becomes more diffuse.
... 5 ...	Luminaire with neutral white colour temperature (4000 K)
... 1 ...	Dimmable luminaire (DALI)
8 668 ...	Luminaire for installation flush with surrounding surface

Accessories Uplight 250, with Tight Lock, externally adjustable optics

Part number	Light distribution	Description
126 0 471 940	narrow beam	Radial louvre, internal (factory fitted), to reduce lateral glare
126 0 472 940	medium wide beam	
126 0 473 940	wide beam	

LED

Luminaires available in 2700 K and other colour temperatures upon request

