

Marbul rec 2xLED GE

142222XX_142223XX

1

Marbul rec 2xLED Warm Dim GE

142225XX

1

driver -

+ driver

Ø108

Ø108 mm

120 mm

WARM DIM

ELECTRICAL SPECS LED-FIXTURE

Drive Current (mA)	Forward Voltage		Power (W)
	min (Vf)	max (Vf)	
350	30,6	37	11,8
+ RED		- BLACK	

For serial connection, respect polarity!
Not suited for connection to mains voltage.
Combine with a Modular LED-driver.

320 x 200 mm

68 mm

100 mm

03 - 12/08/2022

2

11mm

0.2 - 4mm²

24 - 12 AWG

320 x 200 mm

68 mm

3

REFLECTOR NOT INCLUDED

REFLECTOR NOT INCLUDED

4

REFLECTOR NOT INCLUDED

REFLECTOR NOT INCLUDED

LIGHT SOURCE - DO NOT TOUCH LED

Touching the LED can result in permanent damage of the light source. The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person.

PREVENTING ELECTROSTATIC DAMAGE

A discharge of static electricity may damage sensitive components. Therefore do not touch the LED nor the stripped parts of the wires with bare hands. Always be properly insulated by using ESD gloves.

DRIVERS & ACCESSORIES

For latest version of driver matrix and available accessories check www.supermodular.com or connect with your sales contact.