






**Monocube 4 RGBW
with mounting bracket**

With 5 x high performance LEDs RGBW, external DMX-controller required, integral temperature monitoring device, protection class I, IP65 , IK08 windage area A_W 0.02 m² corrosion-resistant die cast aluminium housing AlSi12, polyester powder coated, precise PMMA optics, all exterior steel parts are stainless steel, tempered safety glass, silicon gasket, closure with 4 stainless steel screws, mounting bracket: 2 drilled holes Ø 7 mm, spacing 30 - 40 mm, 1 centre hole Ø 17 mm, tilt range 180°, 2 x M20 cable gland, RDM compatible integral driver (AC/DC)



Monocube 4 RGBW, narrow beam

Part number*	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)
8 264 049 019	black	2.8 kg	5 x LED RGBW	max.	16°
8 264 069 019	white		W = 3000 K	1753 lm	
8 264 059 019	silver grey		(max. 48 W)		




Monocube 4 RGBW, linear beam spread, vertical


Part number*	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)
8 264 049 029	black	2.8 kg	5 x LED RGBW	max.	C 0 - 180 C 90 - 270
8 264 069 029	white		W = 3000 K	1753 lm	33° 16°
8 264 059 029	silver grey		(max. 48 W)		




Monocube 4 RGBW, linear beam spread, horizontal

Part number*	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)
8 264 049 039	black	2.8 kg	5 x LED RGBW	max.	C 0 - 180 C 90 - 270
8 264 069 039	white		W = 3000 K	1753 lm	16° 33°
8 264 059 039	silver grey		(max. 48 W)		




Accessories Monocube 4 external, **for retro-fitting**


Part number	Colour	Description
128 0 700 940	black	Telescopic wall arm 300 - 480 mm, aluminium, polyester powder coated
128 0 700 960	white	
128 0 700 950	silver grey	



Part number	Colour	Description
128 0 730 940	black	Telescopic wall arm 440 - 610 mm, aluminium, polyester powder coated
128 0 730 960	white	
128 0 730 950	silver grey	




Part number	Colour	Description
129 0 736 940	black	Earth spike, stainless steel, for use in landscaped areas
129 0 736 960	white	
129 0 736 950	silver grey	





Part number	Description
120 0 620 940	Expandable tree strap with mounting plate, made of polyester fiber for trunk circumference max. 140 cm*, with polyester powder coated mounting plate



*different lengths available upon request



Part number	Colour	Description
122 0 524 940	black	Cowl, stainless steel, to avoid glare from 3 directions, for retro-fitting
122 0 524 960	white	
122 0 524 950	silver grey	

Accessories Monocube 4 internal, **factory fitted**

Part number	Description
232 0 599 000	Honeycomb louvre to avoid glare



Part number	Description
122 0 181 000	Diffuser film + for moderate light diffusion
122 0 182 000	Diffuser film + + for medium light diffusion
122 0 183 000	Diffuser film + + + for strong light diffusion
122 0 184 000	Prismatic film for linear beam control, vertical
122 0 185 000	Prismatic film for linear beam control, horizontal

