



SMART ACCESSORIES

TUBED SUSPENSION


You'd rather install a cylindrical than a square or rectangular surface box? The Smart surface tubed is available in a small (86 mm), large (130 mm) and x-large (190 mm) version. What's more, the large and x-large models also come in suspended versions. Combine the sizes and models to make playful creations on the ceiling. In combination with our Kompas and Hoolahoop ceiling bases, Smart tubed suspension is part of your own unique chandelier.

Smart tubed suspension 115 LED GI



LUMINAIRE NOT INCL.

! 500mA DRIVER INCLUDED



TRAILING EDGE DIMMABLE	
black struc	13141132
brushed alu	13141124
white struc	13141109
DALI	
black struc	13141332
brushed alu	13141324
white struc	13141309
1-10V/PUSHDIM	
black struc	13141232
brushed alu	13141224
white struc	13141209


WARM DIM

Smart tubed suspension 115 LED warm dim GI



LUMINAIRE NOT INCL.

! TO BE COMBINED WITH SMART 115 ADJUSTABLE WARM DIM
! 350MA DRIVER INCLUDED




TRAILING EDGE DIMMABLE		1800K - 3000K
black struc	13141532	
white struc	13141509	

Smart tubed suspension 115 LED GE



LUMINAIRE NOT INCL.

! LONGER SUSPENSION CABLE ON REQUEST




black struc	13141432
white struc	13141409

Smart combinations & accessories

SMART 115 - TUBED SUSPENSION							
DESIGN	COLOR	FIX/ADJ.	IP-RATE	TECHNOLOGY	TUBED SUSPENSION Ø115 GE	TUBED SUSPENSION Ø115 GI	
							WARM DIM
Smart cake Smart kup Smart lotis		fix	IP20	LED			
			IP54 ⁽²⁾				
		adj.	IP20	LED			
				LED warm dim			
				GU10			



SMART TUBED SUSPENSION 115					
	GE	GI (500MA)			
		TRAILING EDGE DIMMABLE	1-10V/PUSHDIM	DALI	TRAILING EDGE DIMMABLE
					WARM DIM
black struc	13141432	13141132	13141232	13141332	13141532
brushed alu		13141124	13141224	13141324	
white struc	13141409	13141109	13141209	13141309	13141509

Smart lotis 115 LED GE



1X LED ARRAY INCL. 16.25W


! 3500K ON REQUEST



	2700K / CRI90+			
	15°	25°	40°	65°
black struc	12751232	12751032	12751332	12750032
gold	12751246	12751046	12751346	12750046
white struc	12751209	12751009	12751309	12750009
	3000K / CRI90+			
	15°	25°	40°	65°
black struc	12751432	12751532	12751632	12750132
gold	12751446	12751546	12751646	12750146
white struc	12751409	12751509	12751609	12750109
	4000K / CRI90+			
	15°	25°	40°	65°
black struc	12751732	12751132	12751832	12750232
gold	12751746	12751146	12751846	12750246
white struc	12751709	12751109	12751809	12750209
LUMINAIRE OUTPUT & POWER CONSUMPTION				
(white struc)				
	350mA	500mA		
2700K / 25°	1065lm / 11W	1461lm / 16.25W		
3000K / 25°	1046lm / 11W	1434lm / 16.25W		
4000K / 25°	1219lm / 11W	1672lm / 16.25W		



⁽²⁾ Only combination with Smart surface tubed is IP54

Smart cake 115 LED GE




1X LED ARRAY INCL. 16.25W

! 3500K ON REQUEST





Smart kup 115 LED GE



1X LED ARRAY INCL. 16.25W

! 3500K ON REQUEST



	2700K / CRI90+			
	15°	25°	40°	65°
black struc	12741232	12741032	12741332	12740032
gold	12741246	12741046	12741346	12740046
white struc	12741209	12741009	12741309	12740009
	3000K / CRI90+			
	15°	25°	40°	65°
black struc	12741432	12741532	12741632	12740132
gold	12741446	12741546	12741646	12740146
white struc	12741409	12741509	12741609	12740109
	4000K / CRI90+			
	15°	25°	40°	65°
black struc	12741732	12741132	12741832	12740232
gold	12741746	12741146	12741846	12740246
white struc	12741709	12741109	12741809	12740209

LUMINAIRE OUTPUT & POWER CONSUMPTION
(white struc)

	350mA	500mA
2700K / 25°	1019lm / 11W	1397lm / 16.25W
3000K / 25°	1000lm / 11W	1372lm / 16.25W
4000K / 25°	1166lm / 11W	1599lm / 16.25W



	2700K / CRI90+			
	15°	25°	40°	65°
black struc	12761232	12761032	12761332	12760032
gold	12761246	12761046	12761346	12760046
white struc	12761209	12761009	12761309	12760009
	3000K / CRI90+			
	15°	25°	40°	65°
black struc	12761432	12761532	12761632	12760132
gold	12761446	12761546	12761646	12760146
white struc	12761409	12761509	12761609	12760109
	4000K / CRI90+			
	15°	25°	40°	65°
black struc	12761732	12761132	12761832	12760232
gold	12761746	12761146	12761846	12760246
white struc	12761709	12761109	12761809	12760209

LUMINAIRE OUTPUT & POWER CONSUMPTION
(white struc)

	350mA	500mA
2700K / 25°	1065lm / 11W	1461lm / 16.25W
3000K / 25°	1046lm / 11W	1434lm / 16.25W
4000K / 25°	1219lm / 11W	1672lm / 16.25W