





WINK

Design — Couvreur-Devos

Wink may be recessed, and therefore discreet, but its technical ingenuity is nothing short of remarkable. So is its sense of humour. As its name suggests, it likes to wink at you. The streamlined design, where elegance meets high-quality finish, results in a fixture that is half hidden in the ceiling and half peeking out.

Down to the last detail

There's also Wink 82, and a Wink accessory: Wink flange. Compatible with all Wink lamps, Wink flange adds an extra accent in the form of a low ring around the spot, rather than a completely seamless installation. Its precision-designed conical shape complements the spot, enabling it to have a quiet conversation with the ceiling. Because of this accessory, Wink can now be also installed in concrete ceilings.


Refined finishing

Wink generates a symmetrical downwards facing beam of light. Asy Wink, however, emits light asymmetrically. While both look the same, they create a completely different light effect. The asymmetrical light allows you to really emphasise objects on the wall.

Unique light effect

With its symmetric or asymmetric lighting experience, Wink is perfect for any residential or hospitality project. Its uniform design allows you to combine both versions, in order to create different lighting effects in the same room. Have a go with this versatile lighting solution.

Wink asy 115 LED GE




1X LED ARRAY INCL. 16.2W

! MUST BE USED WITH RECESSED RING OR FLANGE
! LED LIGHT IS INSERTED AT A 30° ANGLE

DRIVER > SEE PRODUCT PAGE ON WEBSITE

CONNECTED > SEE GOODIES


INSTALLATION ACCESSORIES



13073009 WINK 115 FLANGE WHSTR (FALSE/CONCRETE CEILINGS)

13073032 WINK 115 FLANGE BLSTR (FALSE/CONCRETE CEILINGS)

14204030 RECESSED RING Ø146 (FALSE CEILINGS)



h 355° ø 133 h 100 (Wink flange)
ø 146 h 100 (Recessed ring)




	2700K / CRI90+			3000K / CRI90+		
	15°	25°	40°	15°	25°	40°
black struc	13071032	13071332	13071632	13071132	13071432	13071732
white struc	13071009	13071309	13071609	13071109	13071409	13071709

LUMINAIRE OUTPUT & POWER CONSUMPTION
(white struc)

	350mA	500mA	700mA
2700K / 25°	776lm / 11W	1023lm / 16.2W	1283lm / 23.4W
3000K / 25°	893lm / 11W	1177lm / 16.2W	1477lm / 23.4W

Wink asy 115 LED spreadlight GE



1X LED ARRAY INCL. 16.2W

! MUST BE USED WITH RECESSED RING OR FLANGE
! LED LIGHT IS INSERTED AT A 30° ANGLE

DRIVER > SEE PRODUCT PAGE ON WEBSITE


CONNECTED > SEE GOODIES

INSTALLATION ACCESSORIES

13073009 WINK 115 FLANGE WHSTR (FALSE/CONCRETE CEILINGS)

13073032 WINK 115 FLANGE BLSTR (FALSE/CONCRETE CEILINGS)

14204030 RECESSED RING Ø146 (FALSE CEILINGS)



h 355° ø 133 h 100 (Wink flange)
ø 146 h 100 (Recessed ring)



	2700K / CRI90+	3000K / CRI90+
black struc	13071932	13072032
white struc	13071909	13072009

LUMINAIRE OUTPUT & POWER CONSUMPTION
(white struc)

	350mA	500mA	700mA
2700K	805lm / 11W	1061lm / 16.2W	1331lm / 23.4W
3000K	791lm / 11W	1042lm / 16.2W	1307lm / 23.4W

Wink 115 LED GE



1X LED ARRAY INCL. 16.2W


! MUST BE USED WITH RECESSED RING OR FLANGE

DRIVER > SEE PRODUCT PAGE ON WEBSITE

CONNECTED > SEE GOODIES

INSTALLATION ACCESSORIES

13073009	WINK 115 FLANGE WHSTR (FALSE/CONCRETE CEILINGS)
13073032	WINK 115 FLANGE BLSTR (FALSE/CONCRETE CEILINGS)
14204030	RECESSED RING Ø146 (FALSE CEILINGS)



	2700K / CRI90+			3000K / CRI90+		
	15°	25°	40°	15°	25°	40°
black struc	13070032	13070332	13070632	13070132	13070432	13070732
white struc	13070009	13070309	13070609	13070109	13070409	13070709

LUMINAIRE OUTPUT & POWER CONSUMPTION
(white struc)

	350mA	500mA	700mA
2700K / 25°	833lm / 11W	1142lm / 16.2W	1520lm / 23.4W
3000K / 25°	952lm / 11W	1306lm / 16.2W	1738lm / 23.4W