





WINK

Design — Couvreur-Devos

Wink may be recessed, and therefore discreet, but its technical ingenuity is nothing short of remarkable. So is its sense of humour. As its name suggests, it likes to wink at you. The streamlined design, where elegance meets high-quality finish, results in a fixture that is half hidden in the ceiling and half peeking out.

Down to the last detail

There's also Wink 82, and a Wink accessory: Wink flange. Compatible with all Wink lamps, Wink flange adds an extra accent in the form of a low ring around the spot, rather than a completely seamless installation. Its precision-designed conical shape complements the spot, enabling it to have a quiet conversation with the ceiling. Because of this accessory, Wink can now be also installed in concrete ceilings.



Refined finishing

Wink generates a symmetrical downwards facing beam of light. Asy Wink, however, emits light asymmetrically. While both look the same, they create a completely different light effect. The asymmetrical light allows you to really emphasise objects on the wall.

Unique light effect

With its symmetric or asymmetric lighting experience, Wink is perfect for any residential or hospitality project. Its uniform design allows you to combine both versions, in order to create different lighting effects in the same room. Have a go with this versatile lighting solution.

Wink asy 82 LED GE





1X LED ARRAY INCL. 9.2W

! MUST BE USED WITH RECESSED RING OR FLANGE
! LED LIGHT IS INSERTED AT A 30° ANGLE

DRIVER > SEE PRODUCT PAGE ON WEBSITE



CONNECTED > SEE GOODIES

INSTALLATION ACCESSORIES



14203009	WINK 82 FLANGE WHSTR (FALSE/CONCRETE CEILINGS)
14203030	RECESSED RING Ø110 (FALSE CEILINGS)
14203032	WINK 82 FLANGE BLSTR (FALSE/CONCRETE CEILINGS)

Wink asy 82 LED spreadlight GE



1X LED ARRAY INCL. 9.2W

! MUST BE USED WITH RECESSED RING OR FLANGE
! LED LIGHT IS INSERTED AT A 30° ANGLE

DRIVER > SEE PRODUCT PAGE ON WEBSITE

CONNECTED > SEE GOODIES

INSTALLATION ACCESSORIES

14203009	WINK 82 FLANGE WHSTR (FALSE/CONCRETE CEILINGS)
14203030	RECESSED RING Ø110 (FALSE CEILINGS)
14203032	WINK 82 FLANGE BLSTR (FALSE/CONCRETE CEILINGS)



	2700K / CRI90+			3000K / CRI90+		
	15°	25°	40°	15°	25°	40°
black struc	14201032	14201132	14201232	14201332	14201432	14201532
white struc	14201009	14201109	14201209	14201309	14201409	14201509

LUMINAIRE OUTPUT & POWER CONSUMPTION
(white struc)

	350mA	500mA
2700K / 25°	520lm / 6.2W	698lm / 9.2W
3000K / 25°	541lm / 6.2W	726lm / 9.2W



	2700K / CRI90+	3000K / CRI90+
black struc	14202032	14202132
white struc	14202009	14202109

LUMINAIRE OUTPUT & POWER CONSUMPTION
(white struc)

	350mA	500mA
2700K	432lm / 6.2W	580lm / 9.2W
3000K	449lm / 6.2W	603lm / 9.2W

Wink 82 LED GE



1X LED ARRAY INCL. 9.2W


! MUST BE USED WITH RECESSED RING OR FLANGE

DRIVER > SEE PRODUCT PAGE ON WEBSITE

CONNECTED > SEE GOODIES

INSTALLATION ACCESSORIES

14203009	WINK 82 FLANGE WHSTR (FALSE/CONCRETE CEILINGS)
14203030	RECESSED RING Ø110 (FALSE CEILINGS)
14203032	WINK 82 FLANGE BLSTR (FALSE/CONCRETE CEILINGS)



	2700K / CRI90+			3000K / CRI90+		
	15°	25°	40°	15°	25°	40°
black struc	14200032	14200132	14200232	14200332	14200432	14200532
white struc	14200009	14200109	14200209	14200309	14200409	14200509

LUMINAIRE OUTPUT & POWER CONSUMPTION
(white struc)

	350mA	500mA
2700K / 25°	493lm / 6.2W	662lm / 9.2W
3000K / 25°	512lm / 6.2W	688lm / 9.2W