




SMART ACCESSORIES

SURFACE TUBED

You'd rather install a cylindrical than a square or rectangular surface box? The Smart surface tubed is available in a small (86 mm), large (130 mm) and x-large (190 mm) version. What's more, the large and x-large models also come in suspended versions. Combine the sizes and models to make playful creations on the ceiling. In combination with our Kompas and Hoolahoop ceiling bases, Smart tubed suspension is part of your own unique chandelier.

Smart surface tubed 115 LED GE




LUMINAIRE NOT INCL.

* ONLY WHEN COMBINED WITH SMART 115 LED IP54

black struc	13140432
white struc	13140409

Smart surface tubed 115 LED GI



LUMINAIRE NOT INCL.

* ONLY WHEN COMBINED WITH SMART 115 LED IP54

! 500mA DRIVER INCLUDED


TRAILING EDGE DIMMABLE	
black struc	13140132
brushed alu	13140124
white struc	13140109

DALI	
black struc	13140332
brushed alu	13140324
white struc	13140309

1-10V/PUSHDIM	
black struc	13140232
brushed alu	13140224
white struc	13140209

WARM DIM

Smart surface tubed 115 LED warm dim GI



LUMINAIRE NOT INCL.

! TO BE COMBINED WITH SMART 115 ADJUSTABLE WARM DIM

! 350MA DRIVER INCLUDED


TRAILING EDGE DIMMABLE	1800K - 3000K
black struc	13140532
white struc	13140509

Smart combinations & accessories

SMART 115 - SURFACE TUBED						
DESIGN	COLOR	FIX/ADJ.	IP-RATE	TECHNOLOGY	SURFACE TUBED Ø115 GE	SURFACE TUBED Ø115 GI
						
Smart cake Smart kup Smart lotis		fix	IP20 IP54 ⁽²⁾	LED		
		adj.	IP20	LED		
				LED warm dim		
				GU10		



SMART SURFACE TUBED 115					
	GE	GI (500MA)			
		TRAILING EDGE DIMMABLE	1-10V/PUSHDIM	DALI	TRAILING EDGE DIMMABLE
black struc	13140432	13140132	13140232	13140332	13140532
brushed alu		13140124	13140224	13140324	
white struc	13140409	13140109	13140209	13140309	13140509

Smart lotis 115 LED GE




1X LED ARRAY INCL. 16.25W

! 3500K ON REQUEST



SMART SURFACE TUBED 115




black struc	13140432
white struc	13140409

				
	2700K / CRI90+			
	15°	25°	40°	65°
black struc	12751232	12751032	12751332	12750032
gold	12751246	12751046	12751346	12750046
white struc	12751209	12751009	12751309	12750009
	3000K / CRI90+			
	15°	25°	40°	65°
black struc	12751432	12751532	12751632	12750132
gold	12751446	12751546	12751646	12750146
white struc	12751409	12751509	12751609	12750109
	4000K / CRI90+			
	15°	25°	40°	65°
black struc	12751732	12751132	12751832	12750232
gold	12751746	12751146	12751846	12750246
white struc	12751709	12751109	12751809	12750209
LUMINAIRE OUTPUT & POWER CONSUMPTION (white struc)				
	350mA	500mA		
2700K / 25°	1065lm / 11W	1461lm / 16.25W		
3000K / 25°	1046lm / 11W	1434lm / 16.25W		
4000K / 25°	1219lm / 11W	1672lm / 16.25W		



⁽²⁾ Only combination with Smart surface tubed is IP54

Smart cake 115 LED GE




1X LED ARRAY INCL. 16.25W

! 3500K ON REQUEST




SMART SURFACE TUBED 115





black struc	13140432
white struc	13140409

Smart kup 115 LED GE




1X LED ARRAY INCL. 16.25W

! 3500K ON REQUEST



SMART SURFACE TUBED 115



black struc	13140432
white struc	13140409



	2700K / CRI90+			
	15°	25°	40°	65°
black struc	12741232	12741032	12741332	12740032
gold	12741246	12741046	12741346	12740046
white struc	12741209	12741009	12741309	12740009
	3000K / CRI90+			
	15°	25°	40°	65°
black struc	12741432	12741532	12741632	12740132
gold	12741446	12741546	12741646	12740146
white struc	12741409	12741509	12741609	12740109
	4000K / CRI90+			
	15°	25°	40°	65°
black struc	12741732	12741132	12741832	12740232
gold	12741746	12741146	12741846	12740246
white struc	12741709	12741109	12741809	12740209

LUMINAIRE OUTPUT & POWER CONSUMPTION
(white struc)

	350mA	500mA
2700K / 25°	1019lm / 11W	1397lm / 16.25W
3000K / 25°	1000lm / 11W	1372lm / 16.25W
4000K / 25°	1166lm / 11W	1599lm / 16.25W



	2700K / CRI90+			
	15°	25°	40°	65°
black struc	12761232	12761032	12761332	12760032
gold	12761246	12761046	12761346	12760046
white struc	12761209	12761009	12761309	12760009
	3000K / CRI90+			
	15°	25°	40°	65°
black struc	12761432	12761532	12761632	12760132
gold	12761446	12761546	12761646	12760146
white struc	12761409	12761509	12761609	12760109
	4000K / CRI90+			
	15°	25°	40°	65°
black struc	12761732	12761132	12761832	12760232
gold	12761746	12761146	12761846	12760246
white struc	12761709	12761109	12761809	12760209

LUMINAIRE OUTPUT & POWER CONSUMPTION
(white struc)

	350mA	500mA
2700K / 25°	1065lm / 11W	1461lm / 16.25W
3000K / 25°	1046lm / 11W	1434lm / 16.25W
4000K / 25°	1219lm / 11W	1672lm / 16.25W