



Monospot Mini


With high performance LED,
CRI: > 80, Colour tolerance: max. 2 SDCM
Service life: L90/B10 > 50 000 h
protection class I, IP65 , IK08
windage area A_W 0.006 m²
corrosion-resistant die cast aluminium housing AlSi12,
polyester powder coated,
precise PMMA optic,
all exterior steel parts are stainless steel,
tempered high transmission safety glass,
silicon gasket,
mounting bracket powder coated aluminium:
1 elongated hole Ø 7 mm, spacing 15 mm,
1 centre hole Ø 8.5 mm, tilt range 180°,
M16 cable gland,
integral driver (AC/DC)

Monospot Mini, narrow beam

Part number	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)
8 900 046 019	black	0.5 kg	1 x LED 3 W	128 lm	4°
8 900 066 019	white		warm white (3000 K)		
8 900 056 019	silver grey				





Part number	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)
8 900 045 019	black	0.5 kg	1 x LED 3 W	136 lm	4°
8 900 065 019	white		neutral white (4000 K)		
8 900 055 019	silver grey				





Monospot Mini, linear beam spread, vertical


Part number	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)
8 900 046 029	black	0.5 kg	1 x LED 3 W	130 lm	C 0 – 180
8 900 066 029	white		warm white (3000 K)		24°
8 900 056 029	silver grey				6°



Part number	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)
8 900 045 029	black	0.5 kg	1 x LED 3 W	140 lm	C 0 – 180
8 900 065 029	white		neutral white (4000 K)		24°
8 900 055 029	silver grey				6°





Part number	Description
. 3.	Luminaire with linear beam spread, horizontal




Monospot Mini, medium wide beam

Part number	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)
8 900 046 049	black	0.5 kg	1 x LED 3 W	130 lm	13°
8 900 066 049	white		warm white (3000 K)		
8 900 056 049	silver grey				



Part number	Colour	Weight	Light source	Luminous flux	Beam angle γ (FWHM)
8 900 045 049	black	0.5 kg	1 x LED 3 W	142 lm	13°
8 900 065 049	white		neutral white (4000 K)		
8 900 055 049	silver grey				



LED (see page 247)


luminaires available in 2700 K and other colour temperatures upon request






Accessories for Monospot Mini


Part number	Colour	Description
129 0 699 940	black	Cowl , stainless steel, to avoid lateral glare, for retro-fitting
129 0 699 960	white	
129 0 699 950	silver grey	



Part number	Colour	Description
129 0 500 940	black	Wall arm 250 mm , aluminium, polyester powder coated
129 0 500 960	white	
129 0 500 950	silver grey	



Part number	Colour	Description
129 0 731 940	black	Stainless steel earth spike , for use in landscape lighting
129 0 731 960	white	
129 0 731 950	silver grey	



Part number	Colour	Description
128 0 760 940	black	Pole clamp , aluminium, polyester powder coated, stainless steel strap, for mounting on poles Ø 60 - 120 mm
128 0 760 960	white	
128 0 760 950	silver grey	