

B4 FOURdown

General Recessed Downlight Range






B4 FOURdown

- lense optic available in 18°, 25°, 30°, 50°, 60° <19 UGR
- Various wattages 9W, 11W, 13W, 18W, 25W, 38W & 52W LED modules
- Available in white & black matt textured finishes or custom RAL colours with black, silver or white reflectors
- 2700K, 3000K, 4000K
- 4 Sizes available from 75mm up to 200mm diameter designed as direct fluorescent downlight replacements
- Estimated lifetime of L80 / 50,000h
- Remote constant current drivers available in Non-Dim, 1-10V, DMX, DALI or Casambi



B4 FOURdown

General Recessed Downlight Range

B4-FD75	B4-FD100	B4-FD150	B4-FD200
			
D75 	D100 	D150 	D200 
Colour / CCT 27K / 30K / 40K Wattages 7.5W / 11W up to 950 @ 4K (delivered) 90CRI 3-step MacAdam 25°, 50° Lens options Accessories - white, black or silver reflector	Colour / CCT 27K / 30K / 40K Wattages 9W / 13W up to 320 1600lm @ 4K (delivered) 90CRI 3-step MacAdam 30°, 50° Lens options Accessories - white, black or silver reflector	Colour / CCT 27K / 30K / 40K Wattages 18W / 25W up to 3300lm @ 4K (delivered) 90CRI 3-step MacAdam 30°, 60° Lens options Accessories - white, black or silver reflector	Colour / CCT 27K / 30K / 40K Wattages 25W / 38W / 52W up to 5600lm @ 4K 90CRI 3-step MacAdam 18°, 30°, 60° Lens options Accessories - white, black or silver reflector

B4 FOURdown - (example specification text)

B4 FOURdown 150 recessed LED downlight, 18W 500mA 36fV, IP54, Medium 30° 3000K 90 CRI, White with black reflector, c/w remote Dali driver

B4-FD	150	18W	30	930	WB	DALI
B4-FD	Size	Wattage	Beam	Colour temp	Finish	Control
	75 - 75mm cutout 100 - 100mm cutout 150 - 150mm cutout 200 - 200mm cutout	FD75 7.5W - 7.5W (250mA) 11W - 11W (350mA) FD100 9W - 9W (260mA) 13W - 13W (350mA) FD150 18W - 18W (500mA) 25W - 25W (700mA) FD200 25W - 25W (700mA) 38W - 38W (1050mA) 52W - 52W (1400mA)	FD75 25 - 25° Lens 50 - 50° Lens FD100 30 - 30° Lens 50 - 50° Lens FD150 30 - 30° Lens 60 - 60° Lens FD200 18 - 18° Lens 30 - 30° Lens 60 - 60° Lens	927 - 2700K warm white 930 - 3000K warm white 940 - 4000K cool white	BB - Black / Black reflector BS - Black / Silver reflector BW - Black / White reflector WB - White / Black reflector WS - White / Silver reflector WW - White / White reflector	ND - Non dim DIM - 1-10v DALI - Dali DMX - DMX CAS - Casambi