


Specifications



Material	
Light Source Type	LED
LED Type	BRIDGELUX WARMDIM 4W
LED technology	LED COB
CRI	Min. 95
Colour Temperature	1800-3000K (Warm Dim)
Lifetime	L80B20 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	2
CIE flux code	82 92 97 50 56
Binning (SDCM)	3
Light Direction	Up/Down
Optic	Collimator
Measured beam angle (°)	43.0
Input Voltage	230V
Luminaire power (W)	10.6
Electrical Class	I
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	Trailing Edge
Indoor/Outdoor	Indoor
Application	Wall
Mounting	Surface
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Grey White Structure, Champagne Brushed Ano, Black Chrome, Black Brushed Ano, Silver Bronze Ano, Bronze Brushed Ano
Gross weight (g)	480.0
Delivered lumens (lm)	<482
Efficacy (lm/W)	45
Glare rating	30

Modular L.I. reserves the right to alter material, dimensions and characteristics without prior notice. Lighting technology changes rapidly
 Latest datasheet and documentation available on www.supremodular.com - 2024-02-06, 02:44:16 AM - ©Modular Lighting Instruments