

REBA 50 D/I Line



Product characteristics

- Body**
Extruded aluminium profile
- Finish**
Powder coated
- Optical system**
bGLARE - Microprismatic diffuser
bLINE - Opal diffuser
ASYM - Asymmetric diffuser
- Light source**
LED, RG1, CRI>80, MacAdam Step ≤3
- LED lifetime**
80.000h @ L90, B10, Ta 25°C
- Control gear**
LED driver 220-240V-50/60Hz included

CE	RoHS	
230V/50Hz	IP 40	
ASYM 850°C	bGLARE 850°C	bLINE 960°C

01. Select Outer Profile



OUTER PROFILE		
Start / End (SRT/END)		
	Lmm	CODE*
	1127	90508L0040▲0083
	1407	90508L0050▲0083
	1687	90508L0060▲0083
	2249	90508L0080▲0083
	2529	90508L0090▲0083
	2809	90508L0100▲0083
Middle (MID)		
	Lmm	CODE*
	1122	90508L0040▲0000
	1402	90508L0050▲0000
	1682	90508L0060▲0000
	2244	90508L0080▲0000
	2524	90508L0090▲0000
	2804	90508L0100▲0000
Horizontal corner (HRZ) - Horizontal edge corner (EDGE)		
	Lmm	CODE*
	601	90508H0040▲0000


*Replace the symbols to complete the code

Colour	▲
□ White	W
■ Grey	G
■ Black	B


OUTER PROFILE	
• The indirect light diffuser is included on the product. • To complete the product add the inner profile. Please order separately. • For suspended version add the suspension, current supply cable and ceiling rose. Please order separately. • To complete the line add the start kit, through-wiring and body connector kit. Please order separately. • Dimensions do not include start kit. To complete the line add 6 mm to the length. • The maximum line length with 1 single feeding point is 15000 mm.	

02. Select Inner and Outer Profile

INNER PROFILE | SYMMETRIC




bGLARE - Microprismatic diffuser (60%/40%)




	W	lm output	lm/W	Lmm	CODE*
	52	5159	99	1120	90528L004♥W0♦00
	65	6633	102	1400	90528L005♥W0♦00
	77	8107	105	1680	90528L006♥W♦♦00
	102	10318	101	2240	90528L008♥W0♦00
	117	11792	101	2520	90528L009♥W0♦00
	130	13266	102	2800	90528L010♥W0♦00
HRZ	45	4422	98	597	90528H004♥W0♦00

bLINE - Opal diffuser (60%/40%)




	W	lm output	lm/W	Lmm	CODE*
	52	5250	101	1120	90527L004♥W0♦00
	65	6749	104	1400	90527L005♥W0♦00
	77	8249	107	1680	90527L006♥W♦♦00
	102	10499	103	2240	90527L008♥W0♦00
	117	11999	103	2520	90527L009♥W0♦00
	130	13499	104	2800	90527L010♥W0♦00
HRZ	45	4500	100	597	90527H004♥W0♦00

INNER PROFILE | ASYMMETRIC



ASYM - Diffuser (60%/40%)



	W	lm output	lm/W	Lmm	CODE*
	51	4707	92	1120	90530L004♥W0♦00
	66	6051	92	1400	90530L005♥W0♦00
	79	7396	94	1680	90530L006♥W♦♦00
	100	9413	94	2240	90530L008♥W0♦00
	117	10758	92	2520	90530L009♥W0♦00
	133	12102	91	2800	90530L010♥W0♦00
EDGE	44	4034	92	597	90530E004♥W0♦00
HRZ	44	4034	92	597	90530H004♥W0♦00



*Replace the symbols to complete the code

Control gear	♥
HF	E
DALI	H
HF+CD ¹	Q
SWD+CD ²	Y

Emergency	●
No EM	0
EM 3h (K3) ³	3

Colour temp.	♦
3000K	3
4000K	0
Tunable White ⁴	T

¹ HF + Double circuit.

² SwitchDIM + Double circuit.

³ Prepared for emergency remote control.

⁴ Only available for the DALI and SWD+CD without emergency unit versions (No EM).

03. Select options

OPTIONS	Code*
SwitchDIM Tunable White • Each SwitchDIM Tunable White allows the control up to 20 luminaires of L ≤ 1682 mm and up to 10 luminaires of L ≥ 1964 mm.	926600
Start kit - end cap start/end • 2 end caps included.	87 50 3 923300▲
Through-wiring • Standard 3 x 1,5 mm ² 4 x 1,5 mm ² 5 x 1,5 mm ²	945650 948400 945750
• 2 x 1,5 mm² HF+K3 (x1) - L562 - L1682 mm HF+K3 (x2) - L1964 - L2804 mm	948000 948001
• 2 x 1,5 mm² + 5P terminal block DALI+K3 (x1) - L562 - L1682 mm DALI+K3 (x2) - L1964 - L2804 mm	948200 948201
• 2 x 1,5 mm² + 2 x 0,75 mm² + 5P terminal block K3+TEL (x1) - L562 - L1682 mm K3+TEL (x2) - L1964 - L2804 mm	948100 948101
Body connector kit • Steel body connector, screws included.	932110
Suspension S5 L1500 mm (x1) S5 L1500 mm (x2) S5 L3000 mm (x1) S5 L3000 mm (x2) S5 L6000 mm (x1) S5 L6000 mm (x2)	910408 910409 910419 910412 910420 910421
Transparent current supply cable 3 x 1,5 mm ² 5 x 1,5 mm ² 7 x 1,5 mm ² • For the option DALI with emergency unit and remote control add 2 current supply cables of 5 x 0,75 mm ² .	94030▲ 94000▲ 94010▲
Square ceiling rose⁵ Surface mounted T25 Surface mounted T29 (DALI+K3)	45 100 978610▲ 978611▲
Recessed T7 Recessed T59 (DALI+K3)	Ø70 35 90 971400▲ 971410▲
Round ceiling rose⁵ Surface mounted T24 Surface mounted T26 (DALI+K3)	45 Ø95 978600▲ 978601▲
Recessed T5 Recessed T27 (DALI+K3)	Ø70 33 Ø90 971300▲ 978700▲
Blank part L1500 mm L3000 mm • Includes inner profile and aluminium blank cover.	992940▲ 992941▲
Low Output version • Under request.	
Bespoke projects • Under request.	



*Replace the symbols to complete the code

Length	▲
L1500 mm	0
L3000 mm	1
L6000 mm	2

Colour⁵	▲
□ White	W
■ Grey	G
■ Black	B



Product details



⁵The ceiling roses are available only in White or Black colour.

