

REBA 50 /E




Product
characteristics

Body Extruded aluminium profile
Finish Powder coated
Fixing system Brackets
Optical system bGLARE - Microprismatic diffuser bLINE - Opal diffuser ASYM - Asymmetric diffuser
Light source LED, RG1, CRI>80, MacAdam Step ≤3
LED lifetime 80.000h @ L90, B10, Ta 25°C
Control gear LED driver 220-240V-50/60Hz included
Ceiling thickness For ceilings between 1-25 mm

CE	RoHS	
230V/50Hz	IP 40	
ASYM 850°C	bGLARE 850°C	bLINE 960°C

01. Select Outer Profile

OUTER PROFILE



Lmm	56	CODE*
590	580	90520L0020▲0000
870	860	90520L0030▲0000
1150	1140	90520L0040▲0000
1430	1420	90520L0050▲0000
1710	1700	90520L0060▲0000
1992	1982	90520L0070▲0000
2272	2262	90520L0080▲0000
2552	2542	90520L0090▲0000
2832	2822	90520L0100▲0000



*Replace the symbols to complete the code


Colour	▲
□ White	W
■ Grey	G
■ Black	B

OUTER PROFILE


• To complete the product add the inner profile. Please order separately.

02. Select Inner and Outer Profile

INNER PROFILE | SYMMETRIC




bGLARE - Microprismatic diffuser




W	lm output	lm/W	Lmm	CODE*
15	1603	107	562	90498L002♥W0♦00
22	2405	109	842	90498L003♥W0♦00
30	3207	107	1122	90498L004♥W♦♦00
35	4008	115	1402	90498L005♥W♦♦00
42	4810	115	1682	90498L006♥W♦♦00
52	5612	108	1964	90498L007♥W♦♦00
60	6413	107	2244	90498L008♥W♦♦00
65	7215	111	2524	90498L009♥W♦♦00
70	8017	115	2804	90498L010♥W♦♦00

bLINE - Opal diffuser



W	lm output	lm/W	Lmm	CODE*
15	1655	110	562	90497L002♥W0♦00
22	2483	113	842	90497L003♥W0♦00
30	3310	110	1122	90497L004♥W♦♦00
35	4138	118	1402	90497L005♥W♦♦00
42	4965	118	1682	90497L006♥W♦♦00
52	5793	111	1964	90497L007♥W♦♦00
60	6620	110	2244	90497L008♥W♦♦00
65	7448	115	2524	90497L009♥W♦♦00
70	8275	118	2804	90497L010♥W♦♦00




*Replace the symbols to complete the code

Control gear	♥
HF	E
DALI	H


Emergency	●
No EM	0
EM 3h (K3) ^{1 2}	3

Colour temp.	♦
3000K	3
4000K	0
Tunable White ³	T

INNER PROFILE | ASYMMETRIC



ASYM - Diffuser



W	lm output	lm/W	Lmm	CODE*
16	1396	87	562	90500L002♥W0♦00
23	2095	91	842	90500L003♥W0♦00
29	2793	96	1122	90500L004♥W♦♦00
36	3491	97	1402	90500L005♥W♦♦00
44	4189	95	1682	90500L006♥W♦♦00
52	4888	94	1964	90500L007♥W♦♦00
58	5586	96	2244	90500L008♥W♦♦00
65	6284	97	2524	90500L009♥W♦♦00
73	6982	96	2804	90500L010♥W♦♦00

¹ Prepared for emergency remote control.

² Versions DALI + EM 3h (K3) only available from L1402 mm.

³ Only available on dimmable DALI versions without emergency unit (No EM). Not available in L562 mm version.

03. Select
options

OPTIONS	Code
SwitchDIM Tunable White • Each SwitchDIM Tunable White allows the control up to 20 luminaires of L ≤ 1682 mm and up to 10 luminaires of L ≥ 1964 mm.	926600
Steel safety cable L1500 mm	955000
Low Output version • Under request.	



Product
details



Outer profile



Brackets




Inner profile symmetric



Inner profile
asymmetric



Light uniformity



Clip-in diffuser



Ceiling recessed
application



bGLARE diffuser



bLINE diffuser



ASYM diffuser



SwitchDIM
Tunable White

