

REBA 50




Product characteristics

- Body**
Extruded aluminium profile
- Finish**
Powder coated
- Optical system**
bGLARE - Microprismatic diffuser
bLINE - Opal diffuser
ASYM - Asymmetric diffuser
- Light source**
LED, RG1, CRI>80, MacAdam Step ≤3
- LED lifetime**
80.000h @ L90, B10, Ta 25°C
- Control gear**
LED driver 220-240V-50/60Hz included

230V/50Hz	IP 40	ASYM 850°C	
bGLARE 850°C	bLINE 960°C		

01. Select Outer Profile

OUTER PROFILE



Lmm	CODE*
578	90517L0020●0000
858	90517L0030●0000
1138	90517L0040●0000
1418	90517L0050●0000
1698	90517L0060●0000
1980	90517L0070●0000
2260	90517L0080●0000
2540	90517L0090●0000
2820	90517L0100●0000

*Replace the symbols to complete the code


Colour	▲
□ White	W
■ Grey	G
■ Black	B

OUTER PROFILE


- To complete the product add the inner profile. Please order separately.
- For suspended version add the suspension, current supply cable and ceiling rose. Please order separately.

02. Seleccionar perfil interior e Diffuser

INNER PROFILE | SYMMETRIC




bGLARE - Microprismatic diffuser



W	lm output	lm/W	Lmm	CODE*
15	1603	107	562	90498L002♥W0♦00
22	2405	109	842	90498L003♥W0♦00
30	3207	107	1122	90498L004♥W0♦00
35	4008	115	1402	90498L005♥W0♦00
42	4810	115	1682	90498L006♥W0♦00
52	5612	108	1964	90498L007♥W0♦00
60	6413	107	2244	90498L008♥W0♦00
65	7215	111	2524	90498L009♥W0♦00
70	8017	115	2804	90498L010♥W0♦00

bLINE - Opal diffuser



W	lm output	lm/W	Lmm	CODE*
15	1655	110	562	90497L002♥W0♦00
22	2483	113	842	90497L003♥W0♦00
30	3310	110	1122	90497L004♥W0♦00
35	4138	118	1402	90497L005♥W0♦00
42	4965	118	1682	90497L006♥W0♦00
52	5793	111	1964	90497L007♥W0♦00
60	6620	110	2244	90497L008♥W0♦00
65	7448	115	2524	90497L009♥W0♦00
70	8275	118	2804	90497L010♥W0♦00


*Replace the symbols to complete the code

Control gear	♥
HF	E
DALI	H


Emergency	●
No EM	0
EM 3h (K3) ^{1 2}	3

Colour temp.	♦
3000K	3
4000K	0
Tunable White ³	T

INNER PROFILE | ASYMMETRIC



ASYM - Diffuser



W	lm output	lm/W	Lmm	CODE*
16	1396	87	562	90500L002♥W0♦00
23	2095	91	842	90500L003♥W0♦00
29	2793	96	1122	90500L004♥W0♦00
36	3491	97	1402	90500L005♥W0♦00
44	4189	95	1682	90500L006♥W0♦00
52	4888	94	1964	90500L007♥W0♦00
58	5586	96	2244	90500L008♥W0♦00
65	6284	97	2524	90500L009♥W0♦00
73	6982	96	2804	90500L010♥W0♦00

¹ Prepared for emergency remote control.

² Versions DALI + EM 3h (K3) only available from L1402 mm.

³ Only available on dimmable DALI versions without emergency unit (No EM). Not available in L562 mm version.

03. Select options

OPTIONS	Code*
SwitchDIM Tunable White • Each SwitchDIM Tunable White allows the control up to 20 luminaires of L ≤ 1682 mm and up to 10 luminaires of L ≥ 1964 mm.	926600
Suspension S5 L1500 mm (x1) S5 L1500 mm (x2) S5 L3000 mm (x1) S5 L3000 mm (x2) S5 L6000 mm (x1) S5 L6000 mm (x2)	910408 910409 910419 910412 910420 910421
Transparent current supply cable L1500 mm - 3 x 0,75 mm ² L1500 mm - 5 x 0,75 mm ² L1500 mm - 7 x 0,75 mm ² L3000 mm - 3 x 0,75 mm ² L3000 mm - 5 x 0,75 mm ² L3000 mm - 7 x 0,75 mm ² L6000 mm - 3 x 0,75 mm ² L6000 mm - 5 x 0,75 mm ² L6000 mm - 7 x 0,75 mm ² • For the option DALI with emergency unit and remote control add 2 current supply cables of 5 x 0,75 mm ² .	940400 940500 940600 940401 940501 940601 940402 940507 940602
Square ceiling rose Surface mounted T25 Surface mounted T29 (DALI+K3)	45 l  100 978610♣ 978611♣
Recessed T7 Recessed T59 (DALI+K3)	Ø70 35 l  90 971400♣ 971410♣
Round ceiling rose Surface mounted T24 Surface mounted T26 (DALI+K3)	45 l  Ø95 978600♣ 978601♣
Recessed T5 Recessed T27 (DALI+K3)	Ø70 33 l  Ø90 971300♣ 978700♣
Low Output version • Under request.	



*Replace the symbols to complete the code

Colour	♣
□ White	W
■ Black	B



Product details



