

REBA 65 /T




Product
characteristics

Body Extruded aluminium profile
Finish Powder coated
Fixing system Trimless recessed mounting kit
Optical system bGLARE - Microprismatic diffuser bLINE - Opal diffuser ASYM - Asymmetric diffuser
Light source LED, RG1, CRI>80, MacAdam Step ≤3
LED lifetime 80.000h @ L90, B10, Ta 25°C
Control gear LED driver 220-240V-50/60Hz included
Ceiling thickness For ceilings between 10, 13, 15 and 18 mm

CE	RoHS	
230V/50Hz	IP 40	
ASYM 850°C	bGLARE 850°C	bLINE 960°C

01. Select Outer Profile

OUTER PROFILE



Lmm	Icon	CODE*
598	600	90524L0020▲0000
878	880	90524L0030▲0000
1158	1160	90524L0040▲0000
1438	1440	90524L0050▲0000
1718	1720	90524L0060▲0000
2000	2002	90524L0070▲0000
2280	2282	90524L0080▲0000
2560	2562	90524L0090▲0000
2840	2842	90524L0100▲0000

*Replace the symbols to complete the code


Colour	Icon
White	W
Grey	G
Black	B

OUTER PROFILE


• To complete the product add the inner profile. Please order separately.

02. Select Inner and Outer Profile

INNER PROFILE | SYMMETRIC



bGLARE - Microprismatic diffuser




W	lm output	lm/W	Lmm	CODE*
15	1577	105	562	90502L002♥W0♦00
22	2366	108	842	90502L003♥W0♦00
30	3155	105	1122	90502L004♥W♦♦00
35	3944	113	1402	90502L005♥W♦♦00
42	4732	113	1682	90502L006♥W♦♦00
52	5521	106	1964	90502L007♥W♦♦00
60	6310	105	2244	90502L008♥W♦♦00
65	7099	109	2524	90502L009♥W♦♦00
70	7887	113	2804	90502L010♥W♦♦00

*Replace the symbols to complete the code


Control gear	Icon
HF	E
DALI	H

Emergency	Icon
No EM	0
EM 3h (K3) ^{1 2}	3

Colour temp.	Icon
3000K	3
4000K	0
Tunable White ³	T




bLINE - Opal diffuser




W	lm output	lm/W	Lmm	CODE*
15	1681	112	562	90501L002♥W0♦00
22	2521	115	842	90501L003♥W0♦00
30	3362	112	1122	90501L004♥W♦♦00
35	4202	120	1402	90501L005♥W♦♦00
42	5043	120	1682	90501L006♥W♦♦00
52	5883	113	1964	90501L007♥W♦♦00
60	6724	112	2244	90501L008♥W♦♦00
65	7564	116	2524	90501L009♥W♦♦00
70	8405	120	2804	90501L010♥W♦♦00

INNER PROFILE | ASYMMETRIC



ASYM - Diffuser



W	lm output	lm/W	Lmm	CODE*
16	1474	92	562	90504L002♥W0♦00
23	2211	96	842	90504L003♥W0♦00
29	2948	102	1122	90504L004♥W♦♦00
36	3685	102	1402	90504L005♥W♦♦00
44	4422	101	1682	90504L006♥W♦♦00
52	5159	99	1964	90504L007♥W♦♦00
58	5896	102	2244	90504L008♥W♦♦00
65	6633	102	2524	90504L009♥W♦♦00
73	7370	101	2804	90504L010♥W♦♦00

¹ Prepared for emergency remote control.

² Versions DALI + EM 3h (K3) only available from L1402 mm.

³ Only available on dimmable DALI versions without emergency unit (No EM). Not available in L562 mm version.

03. Select
options

OPTIONS	Code
SwitchDIM Tunable White • Each SwitchDIM Tunable White allows the control up to 20 luminaires of L ≤ 1682 mm and up to 10 luminaires of L ≥ 1964 mm.	926600
Steel safety cable L1500 mm	955000
Low Output version • Under request.	



Product
details




Outer profile



Inner profile symmetric




Inner profile
asymmetric




Light uniformity



Trimless recessed
mounting kit



Clip-in diffuser



Trimless application



bGLARE diffuser



bLINE diffuser



ASYM diffuser



SwitchDIM
Tunable White

