

B4 FOURdisc

Surface Mounted Round Range





B4 FOURdisc

- Opal & Micro Prismatic diffuser options
- 4 diameter options, 350mm, 450mm, 600mm, 900mm
- CRI90, UGR<19
- 2700K, 3000K, 4000K (3500K on request)
- Integral Non-Dim, 1-10V, DALI or Casambi
- Slim 50mm height profile, offset 30mm from the ceiling by the gear housing creating a shadowline above the fitting



B4 FOURdisc

Surface Mounted Round Range

B4-FD-SM-350-XP-18W-9X0	B4-FD-SM-450-XP-26W-9X0	B4-FD-600-XP-50W-9X0	B4-FD-SM-900-XP-68W-9X0
			
			
Options 2700K / 3000K / 4000K 14W / 18W up to 2200lm @ 4K 90CRI 3-step MacAdam UGR<19 Opal or Microprismatic diffuser	Options 2700K / 3000K / 4000K 18W / 26W up to 3000lm @ 4K 90CRI 3-step MacAdam UGR<19 Opal or Microprismatic diffuser	Options 2700K / 3000K / 4000K 40W / 50W up to 6500lm @ 4K 90CRI 3-step MacAdam UGR<19 Opal or Microprismatic diffuser	Options 2700K / 3000K / 4000K 68W up to 8500lm @ 4K 90CRI 3-step MacAdam UGR<19 Opal or Microprismatic diffuser

B4 FOURdisc - (example specification text)

B4 FOURdisc 450mm surface mounted luminaire, 26W CRI90+ 3000K, black powdercoated finish with opal diffuser, IP20, integrated Dali gear

B4-FD	SM	450	OP	26W	930	DALI	B
B4-FD	Type	Size	Diffuser	Wattage	Colour temp	Control	Finish
	SM - Surface Mounted	350 - 350mm diam 450 - 450mm diam 600 - 600mm diam 900 - 900mm diam	OP - Opal diffuser MP - Micro Prismatic diffuser	350MM 14W - 14W 18W - 18W 450MM 18W - 18W 26W - 26W 600MM 40W - 40W 50W - 50W 900MM 68W - 68W	927 - 2700K 930 - 3000K 940 - 4000K	ND - Non dim DIM - 1-10v DALI - Dali CAS - Casambi	W - White B - Black RAL - RAL
							
Micro Prismatic Diffuser		Opal Diffuser					