


oto reading light



|                                   |  | Colour | Light source | Basic code      | 8030<br>3000K | 8040<br>4000K | TD<br>Dimmable, on stand | Order number                         |
|-----------------------------------|--|--------|--------------|-----------------|---------------|---------------|--------------------------|--------------------------------------|
| <div><div></div><div></div></div> |  | WE     | ①            | <u>0T001-15</u> | ●             | ●             | ●                        | 0T001-15-9027-TD<br>0T001-15-9030-TD |
|                                   |  | SW     | ①            | <u>0T001-18</u> | ●             | ●             | ●                        | 0T001-18-9027-TD<br>0T001-18-9030-TD |
|                                   |  | TB     | ①            | <u>0T001-22</u> | ●             | ●             | ●                        | 0T001-22-9027-TD<br>0T001-22-9030-TD |
|                                   |  | SB     | ①            | <u>0T001-25</u> | ●             | ●             | ●                        | 0T001-25-9027-TD<br>0T001-25-9030-TD |
|                                   |  | ZG     | ①            | <u>0T001-28</u> | ●             | ●             | ●                        | 0T001-28-9027-TD<br>0T001-28-9030-TD |

oto reading light Ø300mm  
Material: Silicone, aluminum, textile-coated cable ~3m

**REMARKS**  
dimmer integrated in luminaire head. Separate controls for ambient and reading light.  
The colours of the textile cable match the luminaires colours

**WE:** White, matt, structured  
**SW:** Black, matt, structured  
**TB:** Dark blue, glossy  
**SB:** Sand beige, glossy  
**ZG:** Cement grey, glossy  
⊕ IP 20

|   |     | CRI      | CCT        | Wattage | Lumen@4000K |
|---|-----|----------|------------|---------|-------------|
| ① | LED | CRI > 90 | 2700/3000K | TBC     | TBC         |