

erluna

**fade midi
adjustable
origin natural**

circular product





IP65
IP54



UK
CA

fade midi adjustable

origin natural



fade midi adjustable

origin natural

When an old Orluna light comes to the end of its life, or is faulty, instead of throwing it away, we kindly ask you to return it to us.

1

The fully repaired and tested product enters back into our stock –with a brand new warranty.

3



The 'new' light fitting is despatched to a new customer.

4

Once we've received the unwanted or faulty fitting, it's dismantled, repaired and renewed with a new LED and PCB.

2



circular product

orluna



fade midi adjustable
origin natural

circular product

		2700K				
		SOFT				
		Spot	Narrow	Medium	Wide	Flood
LIGHT VALUES	Beam Width FWHM	12°	18°	24°	37°	45°
	Source Lumens	858	858	858	858	858
	Engine Lumens	332	637	671	678	679
	Luminaire Lumens	305	564	621	636	633
	Source Lm/CW *1	89	89	89	89	89
	Luminaire Lm/CW *2	31	58	64	66	65
	Luminiare Cd	3885	4169	3322	1655	1154
POWER	Voltage	34.6V				
	Drive Current	250mA				
	Circuit Power (typ)	9.7W				

*1 Part L1 (Residential) *2 Part L2 (Commercial)

		3000K				
		SOFT				
		Spot	Narrow	Medium	Wide	Flood
LIGHT VALUES	Beam Width FWHM	12°	18°	24°	37°	45°
	Source Lumens	915	915	915	915	915
	Engine Lumens	354	728	766	774	775
	Luminaire Lumens	325	602	662	678	675
	Source Lm/CW *1	94	94	94	94	94
	Luminaire Lm/CW *2	34	62	68	70	70
	Luminiare Cd	4145	4448	3544	1766	1231
POWER	Voltage	34.6V				
	Drive Current	250mA				
	Circuit Power (typ)	9.7W				

*1 Part L1 (Residential) *2 Part L2 (Commercial)

DRIVER	Binning	SDCM (Hot)	2
	CRI (typ)(R9)		98 (99)
	TM30 Rf Rg		Rf 97.7 Rg 100.4
	Lifetime (TM21)		L90 B5 50,000hrs (inc driver)
	Protocols	Mains Dim / DALI / 0-10V / Non-dim	
DIMMER	Dim to Dark	0.1% Lux	
	Distance from LED	20m / 65' (series wiring)	
	Emergency	Emergency packs available	

SPECIFICATION CODE

Engine type	Bezel	Colour Temp	Driver	Beam Width	Bezel Colour	Baffle Colour	Options
NL	FDD	27	M	M	W	BB	54 H
		27 / 2700K 30 / 3000K 40 / 4000K*	M / Mains Dim D / DALI 0 / 0-10v N / Non Dim X / No Driver	S / Spot N / Narrow M / Medium W / Wide F / Flood	W / White 9010 D / White RAL 9003 B / Black RAL 9005 C / Other RAL G / Polished Brass K / Brushed Chrome L / Polished Chrome Z / Other Metallic V / Dark Bronze T / Medium Bronze R / Light Bronze Y / Burnished Brass	BB / Black 9005 WB / White RAL 9010 DB / White RAL 9003 CB / Other RAL GB / Polished Brass KB / Brushed Chrome LB / Polished Chrome ZB / Other Metallic	54 / IP54 65 / IP65 H / Honeycomb Louvre K / Click Connector Z / LSZH Cable E / Emergency F / 60 min Fire Rated
		*NOTE: increase 3000k by 7%					