

erluna

**infinity midi trimless
adjustable
zero
high output**

circular product





IP65
IP54



UK
CA

infinity midi trimless adjustable

zero high output



infinity midi trimless adjustable zero high output

When an old Orluna light comes to the end of its life, or is faulty, instead of throwing it away, we kindly ask you to return it to us.

1

The fully repaired and tested product enters back into our stock –with a brand new warranty.

3



The 'new' light fitting is despatched to a new customer.

4

Once we've received the unwanted or faulty fitting, it's dismantled, repaired and renewed with a new LED and PCB.

2



circular product

orluna

infinity midi trimless adjustable
zero high output

circular product

		2700K				
		SOFT				
LIGHT VALUES	Beam Width FWHM	Spot 12°	Narrow 18°	Medium 24°	Wide 37°	Flood 45°
	Source Lumens	1109	1109	1109	1109	1109
	Engine Lumens	429	824	868	877	878
	Luminaire Lumens	410	803	843	855	851
	Source Lm/CW ^{*1}	125	125	125	125	125
	Luminaire Lm/CW ^{*2}	46	90	95	96	96
	Luminaire Cd	5226	5931	4548	2227	1552
POWER	Voltage	31.85V				
	Drive Current	250mA				
	Circuit Power (typ)	8.9W				

^{*1} Part L1 (Residential) ^{*2} Part L2 (Commercial)

		3000K				
		SOFT				
LIGHT VALUES	Beam Width FWHM	Spot 12°	Narrow 18°	Medium 24°	Wide 37°	Flood 45°
	Source Lumens	1155	1155	1155	1155	1155
	Engine Lumens	447	859	904	913	914
	Luminaire Lumens	426	844	869	890	886
	Source Lm/CW ^{*1}	130	130	130	130	130
	Luminaire Lm/CW ^{*2}	48	95	98	100	100
	Luminaire Cd	5443	5954	4730	2319	1617
POWER	Voltage	31.85V				
	Drive Current	250mA				
	Circuit Power (typ)	8.9W				

^{*1} Part L1 (Residential) ^{*2} Part L2 (Commercial)

DRIVER	Binning	SDCM (Hot)
	CRI (typ)(R9)	2 93 (62)
	TM30 Rf Rg	Rf 91 Rg 97
	Lifetime (TM21)	L90 B5 50,000hrs (inc driver)
DRIVER	Protocols	Mains Dim / DALI / 0-10V / Non-dim
	Dim to Dark	0.1% Lux
	Distance from LED	20m / 65' (series wiring)
	Emergency	Emergency packs available

SPECIFICATION CODE

Engine type	Bezel	Colour Temp	Driver	Beam Width	Baffle Colour	Options
ZH	- INFDT -	27 27 / 2700K 30 / 3000K 40 / 4000K*	M M / Mains Dim D / DALI 0 / 0-10v N / Non Dim X / No Driver	M S / Spot N / Narrow M / Medium W / Wide F / Flood	W WB / White 9010 DB / White RAL 9003 CB / Other RAL GB / Polished Brass KB / Brushed Chrome LB / Polished Chrome ZB / Other Metallic VB / Dark Bronze TB / Medium Bronze RB / Light Bronze YB / Burnished Brass AWB / Anodised White 9016 ABB / Anodised Black AVB / Anodised Bronze APB / Anodised Burnished	54 H 54 / IP54 65 / IP65 H / Honeycomb Louvre K / Click Connector Z / LSZH Cable E / Emergency F / 60 min Fire Rated
		*Same output as 3000K				