


Date
Customer
Project
Type

Nyto Semi-Recessed Adjustable 30 lx LED DE




Very subtle, Nyto allows you to add a personal touch to the space or match an existing shade in the interior. With plenty of lighting, colour and application options, Nyto is ideal for many places and spaces.




Specifications

Material	
Light Source Type	LED
LED Type	CITIZEN CLU7S3
LED technology	LED COB
CRI	Min. 90
Colour Temperature	2700K/3000K/3500K & 4000K on request)
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	100 100 100 100 91
Binning (SDCM)	3
Light Direction	Down
Optic	Collimator
Measured beam angle (°)	17.0 (spot) / 25.0 (medium) / 46.0 (Flood)
Input Voltage	Constant Current Driver Required
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Mounting	Semi-Recessed
Cut-out size (mm)	ø40
Mounting depth (mm)	110.0
Adjustability	H 360° V 0°/+90°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Black Structure
Gross weight (g)	191.0
Drive current (mA)	350
Min. forward voltage (Vf)	11.4
Max. forward voltage (Vf)	12.2
Connected load (W)	4.1
Delivered lumens (lm)	374 - 510lm
Efficacy (lm/W)	91
Glare rating	10
Remark	This product comes in different standard and full customisation options. Discover them all on the

Installation Accessories



10889530 Installation Housing 123x100x80



12293130 Plaster Kit 100x120-40 1x

Choose a required accessory