

Date

Customer


Project

Type

Nyto Semi-Recessed Adjustable 50 lx LED DE




Very subtle, Nyto allows you to add a personal touch to the space or match an existing shade in the interior. With plenty of lighting, colour and application options, Nyto is ideal for many places and spaces.




Specifications

Material				
Light Source Type	LED			
LED Type	CITIZEN CLU7S3			
LED technology	LED COB			
CRI	Min. 90			
Colour Temperature	2700K/3000K/(3500K or 4000K on request)			
Lifetime	L70B20 @50,000 Hours			
Lamp Included	Yes			
Number of Light Sources	1			
CIE flux code	100 100 100 100 71			
Binning (SDCM)	3			
Light Direction	Down			
Optic	Collimator			
Measured beam angle (°)	11.0 (Super Spot) / 17.0 (Spot) / 28.0 (Medium) / 44.0 (Flood) / 58.0 (Wide Flood)			
Input Voltage	Constant Current Driver Required			
Electrical Class	III			
IP Rating	20			
Glow wire rating (°C)	960			
Indoor/Outdoor	Indoor			
Application	Ceiling, Wall			
Mounting	Semi-Recessed			
Cut-out size (mm)	ø40			
Mounting depth (mm)	110.0			
Adjustability	H 360° V 0°/+90°			
Distance to Lighted Object (m)	0,1			
Primary Colour & Primary Finish	White, Black Structure			
Gross weight (g)	293.0	F/WF		
Drive current (mA)	350	500	700	900
Min. forward voltage (Vf)	11.4	11.9	12.4	17
Max. forward voltage (Vf)	12.2	12.7	13.2	20.8
Connected load (W)	4.1	6.1	8.9	17
Delivered lumens (lm)	292-617	384-834	483-1061	1101-1124
Efficacy (lm/W)	71	63	54	65
Glare rating	3-17	4-18	5-19	19
Remark	This product comes in different standard and full customisation options. Discover them all on the			

Installation Accessories



10889530 Installation Housing 123x100x80



12293130 Plaster Kit 100x120-40 1x

Choose a required accessory