

ROFY 85 IP /E



Product
characteristics

Body Aluminium
Finish Powder coated
Optical system LIGHT+ - Opal diffuser
Light source LED, RG1, CRI>80, MacAdam Step ≤3
LED lifetime 80.000h @ L90, B10, Ta 25°C
Control gear LED driver 220-240V-50/60Hz included
Ceiling thickness For ceilings between 1-35 mm

CE	RoHS	
230V/50Hz	IP 20/54	
IK 04	650°C	


01. Select version



ROFY 85 IP / E



LIGHT+ - Opal diffuser



W	lm output	lm/W	Dmm		CODE*
16	2135	133	Ø302	Ø286	90573L300▼▲0♦00
24	3385	141	Ø402	Ø386	90573L400▼▲0♦00
43	6516	152	Ø603	Ø586	90573L600▼▲0♦00

*Replace the symbols to complete the code

Control gear	
HF	E
DALI	H

Colour ¹	
White	W
Grey	G
Black	B
Sahara	0
Mist	1
Carbon	I
Autumn	L
Rusty chain	R
Jungle	N
Golden eye	D

Emergency	
No EM	0
EM 3h (K3) ²	3

Colour temp.	
3000K	3
4000K	0
Tunable White ³	T

ROFY 85 IP / E

• This product cannot be installed on the wall.

02. Select options




Product details

OPTIONS Code

Steel safety cable
L1500 mm 955000

Low Output version
• Under request.



Ceiling recessed application

LIGHT+ diffuser

¹ See page 164.

² Prepared for emergency remote control. Only available for the Ø600 mm.

³ Not available in versions Ø300 mm.