

B4 FOURsphere Surface

Opal surface mounted ambient sphere

B4 FOURsphere - Opal surface mounted ambient sphere

- Available in 4 sizes and 4 wattages using dedicated COB LED's
- Opal glass diffuser with surface mounting base finished in black, white or RAL
- Dedicated LED engine with Lumen output options from 342 - 2029lm
- 2700K, 3000K, 3500K & 4000K 90CRI CCT options
- IP20 / (IP54 options for 120mm diameter)
- Supplied with remote Non-Dim, 1-10V, DALI or Casambi drivers



B4 FOURsphere Surface

Opal surface mounted ambient sphere

FOURsphere Surface 120	
FOURsphere Surface 250	
FOURsphere Surface 350	
FOURsphere Surface 450	

FOURsphere Surface 120

- 5W <342lm @260mA
- CRI>90 3-SDCM
- Opal glass diffuser / IP54
- 2700K, 3000K, 3500K, 4000K
- White / black or RAL finish
- Remote Non dim, 1-10V, Dali or Casambi

FOURsphere Surface 250

- 8.1W <1093lm delivered @250mA 32.5Vf
- CRI>90 3-SDCM, Bridgelux V10 COB LED
- Opal glass diffuser / IP20
- 2700K, 3000K, 3500K, 4000K
- White / black or RAL finish
- Remote Non dim, 1-10V, Dali or Casambi

FOURsphere Surface 350

- 16.5W <1594lm delivered @700mA 23.6Vf
- CRI>90 3-SDCM, Xicato XTM COB LED
- Opal glass diffuser / IP20
- 2700K, 3000K, 3500K, 4000K
- White / black or RAL finish
- Remote Non dim, 1-10V, Dali or Casambi

FOURsphere Surface 450

- 25.7W <2029lm delivered @1050mA 24.4Vf
- CRI>90 3-SDCM, Xicato XTM COB LED
- Opal glass diffuser / IP20
- 2700K, 3000K, 3500K, 4000K
- White / black or RAL finish
- Remote Non dim, 1-10V, Dali or Casambi

B4 FOURsphere Surface

Opal surface mounted ambient sphere

B4 FOURsphere - Opal surface mounted ambient sphere

Brand 4 FOURsphere 350mm opal glass sphere surface mount, 8.5w 350mA 19vF CRI90 2700k, IP44, black finish, c/w remote DALI driver

B4-FS	S	350	8W	927	B	DALI
B4-FS	Version	Size	Wattage	Colour temp	Finish	Control
S - Surface	120 - 120mm dia	120	5W - 5W	927 - 2700K warm white	B - Matt Black	ND - Non dim
	250 - 250mm dia	250	8.1W - 8W	930 - 3000K warm white	W - Matt White	DALI - Dali
	350 - 350mm dia	350	16.5W - 17W	935 - 3500K neutral white	RAL - RAL	1-10V - 1-10V
	450 - 450mm dia	450	25.7W - 26W	940 - 4000K cool white		CAS - Casambi

