



VAEDER

Design — Gerd Couckhuyt

more info? supermodular.com/en/vaeder



With a name derived from the English evade, it is clear from the start that Vaeder will be miles ahead of anything average. This fixture feels equally comfortable in an energy-conscious, ergonomic office environment, and in a home office. Its characteristic honeycomb structure in combination with a wafer-thin diffuser, minimizes glare, whilst its ground-breaking LED technology results in an energy-efficient and high-performing luminaire.

Otherworldly

Vaeder is offered as surface mounted or suspended. For surface mounting, it is positioned at a small distance from the ceiling (6 mm), which gives it a lighter look, as if floating against the ceiling. In its pendant version, Vaeder's soft curves create a futuristic fixture that appears to be hovering from another dimension. The fixture's suspension height can be modified using an adjuster system.


UGR16

Because of its unique design consisting of one LED source and three optical components, this luminaire provides bright and glare-free light with an optimal UGR value of 16. This makes Vaeder a perfect LED alternative to office luminaires with the traditional fluorescent T5/T8 lamps. With optimal results on light distribution, visual comfort and efficacy, this luminaire fully meets the EN 12464-1 office standard.

Vaeder LED GI



8X LED LINE INCL. 4W



CONNECTED > SEE GOODIES



DALI/PUSHDIM/1-10V	2700K / CRI90+	3000K / CRI90+	4000K / CRI90+
black struc - black	14080048	14080148	14080248
black struc - white	14080072	14080172	14080272
donkey grey struc - black	14080075	14080175	14080275
donkey grey struc - white	14080074	14080174	14080274
white struc - black	14080029	14080129	14080229
white struc - white	14080073	14080173	14080273


LUMINAIRE OUTPUT & POWER CONSUMPTION
(white struc - white)

2700K / 65°	2303lm / 36W
3000K / 65°	2245lm / 36W
4000K / 65°	2669lm / 36W

Vaeder suspension (power feed surface) LED GI



8X LED LINE INCL. 4W



CONNECTED > SEE GOODIES



DALI/PUSHDIM/1-10V	2700K / CRI90+	3000K / CRI90+	4000K / CRI90+
black struc - black	14081048	14081148	14081348
black struc - white	14081072	14081172	14081372
donkey grey struc - black	14081075	14081175	14081375
donkey grey struc - white	14081074	14081174	14081374
white struc - black	14081029	14081129	14081329
white struc - white	14081073	14081173	14081373


LUMINAIRE OUTPUT & POWER CONSUMPTION
(white struc - white)

2700K / 65°	2303lm / 36W
3000K / 65°	2245lm / 36W
4000K / 65°	2669lm / 36W

Vaeder suspension (power feed recessed) LED GI



8X LED LINE INCL. 4W



CONNECTED > SEE GOODIES



DALI/PUSHDIM/1-10V	2700K / CRI90+	3000K / CRI90+	4000K / CRI90+
black struc - black	14081548	14081248	14081448
black struc - white	14081572	14081272	14081472
donkey grey struc - black	14081575	14081275	14081475
donkey grey struc - white	14081574	14081274	14081474
white struc - black	14081529	14081229	14081429
white struc - white	14081573	14081273	14081473

LUMINAIRE OUTPUT & POWER CONSUMPTION
(white struc - white)

2700K / 65°	2303lm / 36W
3000K / 65°	2245lm / 36W
4000K / 65°	2669lm / 36W