Downlight
NOEL

NOEL is a slim trim LED downlight for general lighting where low glare and a clean ceiling matter. The light source sits deep inside an aluminium alloy housing, so from the floor you see a slim white ring rather than a bright disc. It suits kitchens, living and open-plan areas, offices, reception and retail, and the IP44 rating also covers bathrooms, laundries and covered alfresco areas. The 12W is made for standard ceiling heights and the 15W, 18W for higher ceilings and larger rooms. Four beam angles from 15° to 55° let you go wide for even ambient light or narrow to pick out displays and feature walls. It fits a standard 90mm cutout with flex and plug included, so it drops into renovation holes and new builds alike.





Features

- Narrow trim with slim white housing for a neat, low-profile finish
- High CRI 92 option for accurate colour rendering
- Non-dim is standard, with 0-10V, trailing edge and DALI dimming available
- 90mm cutout, suits common existing downlight holes
- Four beam angles: 15°, 24°, 36° and 55°
- IP44 rated for bathrooms, laundries and covered outdoor areas

Applications

- Living rooms, kitchens and open-plan areas
- Offices, meeting rooms and reception areas
- Hallways, corridors and stairwells
- Retail and showroom general lighting
- Bathrooms and laundries
- Covered alfresco areas and entries



(Side View)



(Top View)

15° | 24° | 36° | 55° | IP 44 | >80 CRI | 92 CRI | AC 200-240V | 3 Yrs Warranty | 35000 @ L90 B10 Lifetime

Product Code	BLDL-NOEL-12	BLDL-NOEL-15	BLDL-NOEL-18
Power (W)	12	15	18
Luminous Flux(lm)	1200	1500	1800
CCT	Warm White, Neutral White, Cool White (2700K-6000K)		
Connect	AU Standard Flex & Plug		
Dimming Options	Various dimming options available on request		
Dimensions(mm)	D97*H73	D97*H94	
Cutout(mm)	D'90		
Weight(kg)	0.3	0.4	