



BoscoLighting's TEX Linear Pendant Light System is a combination of Tetrus anti-glare spotlight and diffused extrusion lighting.

Bold and subtle at the same time, **TEX** is a great way to light up your projects in decorative and practical ways.

Sleek linear profile produces low glare lighting. It is a product that creates an eye-catching statement and inspirational lighting schemes for architectural and commercial projects.

This linear pendant light can be surface mounted as well.

## Applications

- Museums & galleries
- Retail shops
- Libraries
- Residential and commercial projects

## Pendant Light TEX



## Features



- It comes with standard 1.2m lengths, also available at 1.5m on request.
- Straight line joiner and corner joiner available for continuous lines
- Inbuilt constant current power supply(for non-dim)
- Optional dimming on request: Trailing edge dimming or DALI dimming control
- Anodised silver as standard fitting colour. Can be customised in a powder coated white or black finish.(MOQ may apply)



**BLPD-TEX1-12**

50W Low Glare Pendant Light

Power (W): 50  
Luminous Flux (lm): 2950  
Connect: AU Standard Flex & Plug  
CCT: 3000K-6500K  
CRI: >80 (default) or 92  
Viewing Angle: 15/30/45  
Dimming: Non-dim, Trailing edge, DALI  
IP Rating: 40  
Dimensions (mm): L1200\*W54\*H84  
Weight (kg): 2.5



**BLPD-TEX2-12**

47W Low Glare Pendant Light

Power (W): 47  
Luminous Flux (lm): 3185  
Connect: AU Standard Flex & Plug  
CCT: 3000K-6500K  
CRI: >80 (default) or 92  
Viewing Angle: 15/30/45  
Dimming: Non-dim, Trailing edge, DALI  
IP Rating: 40  
Dimensions (mm): L1200\*W54\*H84  
Weight (kg): 2.5



**BLPD-TEX3-12**

30W Low Glare Pendant Light

Power (W): 30  
Luminous Flux (lm): 1755  
Connect: AU Standard Flex & Plug  
CCT: 3000K-6500K  
CRI: >80 (default) or 92  
Viewing Angle: 15/30/45  
Dimming: Non-dim, Trailing edge, DALI  
IP Rating: 40  
Dimensions (mm): L1200\*W54\*H84  
Weight (kg): 2.5

