

Housed in an IP65 rated fitting, GKP08 series is able to be used both indoors and outdoors with protection against moist environment.

It is suitable for residential apartments and commercial premises.

Fittings can also be supplied with sensors to brighten when motion is detected which is great for irregularly used stockrooms, warehouses or corridors.

Features

- IP65 rated, suitable for damp location installation
- Easy Installation
- Long lifespan and little maintenance required
- Suitable for both business, commercial & residential installation

Optional Microwave Sensor

General Version (default)	
Detection area	10%/25%/50%/75%/100%
Hold time	5s/30s/90s/3min/20min/30min
Daylight sensor	2lux/10lux/25lux/50lux/Disable

Corridor Version	
Detection area	50%/100%
Hold time	5s/90s/3min/10min
Daylight sensor	5lux/15lux/50lux/Disable
Stand-by period	0s/30s/10min/+∞
Stand-by dimming level	10%/25%



Product Code	BLSM-GKP08-20	BLSM-GKP08-30
Power (W)	20	30
Luminous FLux(lm)	1600	2400
CCT	Warm White, Neutral White, Cool White (3000K-6000K)	
Connect	Insulated Cable	
Dimming Options	None	
Dimensions(mm)	L300*W300*H90	
Weight(kg)	1.7	

Bulkhead Light GKP08

